



COMMANDER

GENERAL PURPOSE, LOW VOLTAGE AC DRIVES
FOR HVAC APPLICATIONS

C200

DRIVE OBSESSED

COMMANDER C200

SIMPLE RELIABLE

MOTOR CONTROL

Control Techniques has set the standards in motor control since 1973.

The Commander C200 delivers benchmark functionality at no added cost to the base drive itself. Plug-in options, dynamic performance, PLC functionality and other advanced features such as fieldbus, Ethernet, and Modbus RTU communications ensure that Commander C200 can deliver more than the average general purpose drive - giving you lower cost solutions and better productivity in your HVAC motor control applications.

Other Commander C200 benefits include:

Enhance up-time and system flexibility

- Flexible system integration and remote diagnostics through optional industrial Ethernet and fieldbus communication
- Flexible I/O expandable with SI-I/O option module
- Enhanced functionality and onboard PLC programming provide a low-cost HVAC system solution, minimizing the need for additional equipment such as PLCs

Open-loop motor control optimized for HVAC applications

- Speed control for fans, pumps and compressors, where their function can be controlled with fieldbus or Ethernet communications
- UL plenum rated when installed with an optional conduit kit and suitable for use in environments with A2L refrigerants
- Built in HVAC features including PID process controller, energy savings modes and resonant skip frequencies



Diagnostic Software

Our **Drive Diagnostics APP** allows users to quickly diagnose faults. In the unlikely event that you get a drive error, download our complimentary Diagnostic Tool APP and input the error code from your drive and you'll be given a solution.

Download our APP at: www.ctdrives.com/diagnostics



*Warranty terms and conditions apply.

WWW.CONTROLTECHNIQUES.COM



COMMANDER C200

ORDERING INFORMATION

115 VAC, Single Phase 50/60 Hz Input, 230 VAC 3-Phase Output					
Commander C200 Order Code*	Input Phase	Normal Duty		Heavy Duty	
		HP	Amps	HP	Amps
C200-01100017A	1	0.33	1.7	0.33	1.7
C200-01100024A	1	0.5	2.4	0.5	2.4
C200-02100042A	1	1	4.2	1	4.2
C200-02100056A	1	1.5	5.6	1.5	5.6
230 VAC, Single & 3-Phase Input, 3-Phase Output, 50/60 Hz Input					
C200-01200017A	1	0.33	1.7	0.33	1.7
C200-01200024A	1	0.5	2.4	0.5	2.4
C200-01200033A	1	0.75	3.3	0.75	3.3
C200-01200042A	1	1	4.2	1	4.2
C200-02200024A	1,3	0.5	2.4	0.5	2.4
C200-02200033A	1,3	0.75	3.3	0.75	3.3
C200-02200042A	1,3	1	4.2	1	4.2
C200-02200056A	1,3	1.5	5.6	1.5	5.6
C200-02200075A	1,3	2	7.5	2	7.5
C200-03200100A	1,3	3	10	3	10
C200-04200133A	1,3	3	13.3	3	13.3
C200-04200176A	3	5	17.6	5	17.6
C200-05200250A	3	10	30	7.5	25
C200-06200330A	3	15	50	10	33
C200-06200440A	3	20	58	15	44
C200-07200610A	3	25	75	20	61
C200-07200750A	3	30	94	25	75
C200-07200830A	3	40	117	30	83
C200-08201160A	3	50	149	40	116
C200-08201320A	3	60	180	50	132
C200-09201760x**	3	75	216	60	176
C200-09202190x**	3	100	266	75	219
460 VAC, Three Phase Input, 3-Phase Output, 50/60 Hz Input					
C200-02400013A	3	0.5	1.3	0.5	1.3
C200-02400018A	3	0.75	1.8	0.75	1.8
C200-02400023A	3	1	2.3	1	2.3
C200-02400032A	3	1.5	3.2	1.5	3.2
C200-02400041A	3	2	4.1	2	4.1
C200-03400056A	3	3	5.6	3	5.6
C200-03400073A	3	3	7.3	3	7.3
C200-03400094A	3	5	9.4	5	9.4
C200-04400135A	3	7.5	13.5	7.5	13.5
C200-04400170A	3	10	17	10	17
C200-05400270A	3	20	30	20	27
C200-05400300A	3	20	30	20	30
C200-06400350A	3	25	38	25	35
C200-06400420A	3	30	48	30	42
C200-06400470A	3	50	63	30	47
C200-07400660A	3	60	79	50	66
C200-07400770A	3	75	94	60	77
C200-07401000A	3	75	112	75	100
C200-08401340A	3	125	155	100	134
C200-08401570A	3	150	184	125	157
C200-09402000x**	3	150	221	150	180
C200-09402240x**	3	200	255	150	211

*Add 10101AB100 to the base order code when ordering standard US (60Hz) default products

**x= A or E (9E frame requires an external AC Line Reactor)

Note: Ratings shown for 3 kHz switching frequency.

575 VAC, 3-Phase Input & Output, 50/60 Hz Input					
Unidrive C200 Order Code*	Input Phase	Normal Duty		Heavy Duty	
		HP	Amps	HP	Amps
C200-05500030A	3	3	3.9	2	3
C200-05500040A	3	5	6.1	3	4
C200-05500069A	3	7.5	10	5	6.9
C200-06500100A	3	10	12	7.5	10
C200-06500150A	3	15	17	10	15
C200-06500190A	3	20	22	15	19
C200-06500230A	3	25	27	20	23
C200-06500290A	3	30	34	25	29
C200-06500350A	3	40	43	30	34
C200-07500440A	3	50	53	40	44
C200-07500550A	3	60	73	50	55
C200-08500630A	3	75	86	60	63
C200-08500860A	3	100	108	75	86
C200-09501040x**	3	125	125	100	104
C200-09501310x**	3	150	150	125	131

Order String - Frame Size Key

Example: C200-XX_ _ _ _ _

XX = Frame Size (01-09 above)

690 V products are also available, for details visit: www.controltechniques.us

OPTIONS AT-A-GLANCE

Option	Description	Order Code
Drive Configuration & Programming	Configuration software	CONNECT
	Drive to PC USB cable (requires a 485 adaptor)	CT-USB-CABLE
	Parameter cloning 4 GB (includes 4 GB SD card)	AI-SMART-ADAPTOR
	Parameter cloning (requires an SD card)	AI-BACKUP-ADAPTOR
Operator Interfaces	8 GB SD card	CTSD8GB
	Remote LCD display	REMOTE-KEYPAD
	Remote LCD display with real-time clock	REMOTE-KEYPAD-RTC
	Remote display cable	UM-LCD-485-XXX***
Input / Output***	Extended I/O	SI-I/O
	Modbus RTU	AI-485-ADAPTOR
	Modbus RTU with 24 V	AI-485-24V-ADAPTOR
	PROFIBUS DP	SI-PROFIBUS
	DeviceNet	SI-DEVICENET
	CANopen	SI-CANOPEN
	PROFINET RT	SI-PROFINET-V2
	EtherCAT	SI-ETHERCAT
	EtherNet/IP, Modbus TCP	SI-ETHERNET
	Powerlink	SI-POWERLINK
	Interbus	SI-INTERBUS-500K, SI-INTERBUS-2M
	Application Programming Software & Diagnostics	MACHINE-CONTROL-STUDIO
Power Accessories	PLC programming	CTSCOPE
	Digital oscilloscope	
	External EMC filter	
	Line & load reactors	
Environmental Protection & Cable Management	Dynamic braking resistors	Consult factory
	UL Type 1 conduit kits	
	Retrofit for Commander SK	
	Fan replacement kits	

***frame sizes 2 and up accept 1 SI option

****Shielded RS485 patch cable, CAT5e, conductive metal RJ45 connectors, XXX=cable length in 5 foot increments (max 330 ft), standard lengths are (005, 010, 015, 025 and 050)

COMMANDER C200

RATINGS & DIMENSIONS

Ratings

Voltage ratings	
100 V - 120 V $\pm 10\%$	✓
200 V - 240 V $\pm 10\%$	✓
380 V - 480 V $\pm 10\%$	✓
500 V - 575 V $\pm 10\%$	✓
500 V - 690 V $\pm 10\%$	✓
Control mode	
Open loop vector or V/Hz control for induction motor control	✓
Open loop Rotor Flux Control for induction motor control (RFC-A)	✓
Active Front End (AFE) power quality converter	✓

Dimensions & Weights

Frame Size	Dimensions H x W x D (in)	Weight (lbs)
01	6.3 x 3.0 x 5.1	1.7
02	8.1 x 3.1 x 5.9	2.2
03	8.9 x 3.5 x 6.3	3.3
04	10.9 x 4.5 x 6.9	6.9
05	15.4 x 5.6 x 7.9	16.3
06	15.4 x 8.3 x 9.0	30.9
07	21.9 x 10.6 x 11.0	61.7
08	31.7 x 12.2 x 11.4	114.6
09E	39.8 x 12.2 x 11.4	101.4
09A	43.6 x 12.2 x 11.4	146.6

Additional distance should be added to the height dimension (H) when the AI options are fitted.



Heavy Duty Ratings:	0.33 HP to 150 HP (0.25 kW to 110 kW)
Normal Duty Ratings:	0.33 HP to 200 HP (0.25 kW to 132 kW)
Supply phases:	Frame size 1 and 2: 115 V drives 1Ø, 230 V drives 1Ø or 3Ø; Frame size 7 and larger 3Ø; 460, 575 and 690 V drives 3Ø
Control connections:	2x Analog inputs, 4x Digital inputs, 1x Analog output, 1x Digital I/O, 1x Relay
Drive rating:	IP21 / UL open class as standard, UL Type 1 plenum rated when installed with an optional conduit box
Keypad:	Fixed LED
Option slots:	1 (frame size 2 and above)
Parameter cloning via:	PC tools, SD card

Visit www.Drive-Setup.com for step-by-step guides, videos, software & product support documentation.

How to select a drive

(Consult online catalog for complete drive information)

1. Electrical Considerations

- What is the supply voltage?
- Single or 3Ø input power?
- What is the motor rating?
 - Continuous current – FLA (Full Load Amps)
 - Select the drive based on motor Amps rather than horsepower

2. Load Type (choose one)

- Normal Duty: Peak current is 110% of drive rating (fans, pumps, etc.)
- Heavy Duty: Peak current is 180% (compressors, etc.)

3. Drive Mechanical Mounting

- Panel mounting – as standard
- Wall and plenum mounting – UL conduit kits are available
- Through panel mounting – frames 5 and up

Nidec

© 2022 Control Techniques a Nidec Motor Corporation business. The information contained in this brochure is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as Control Techniques has an ongoing process of development and reserves the right to change the specifications of its products without notice.

Control Techniques Americas. Registered Office: 12095 NW 39th Street, Coral Springs, FL 33065 USA

+1 800 893-2321

Part No. FLI-C200-HVAC 01/23