

Totally Enclosed Fan Cooled Pool and Spa Motors Switchless Design, 6.5" Frame Diameter, Category "S" & "J"



FEATURES:

- Shaft Threads – (Square Flange) 1/2-20 UNC-2A or (C-Flange) 7/16-20 UNF-2A
- 50°C Ambient
- 1081 Design
- Continuous Duty
- Class B Insulated
- Totally Enclosed, Fan Cooled
- 300 Series Stainless Steel Shaft
- Thermally Protected
- 6.5" Diameter Frame
- Triple Bearing Protection

**Superior Environmental
Protection**

Square-Flange, Premium Energy Efficient, Total Horsepower Rated, Category "S"

THP	RPM	Voltage	Freq	Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
1.25	3450	208-230/115	60	5.9-5.5/11.0	ETE661	56Y	11.27	30
1.65	3450	208-230/115	60	7.6-7.2/14.4	ETE841	56Y	11.27	31
2.25	3450	208-230/115	60	9.7-9.0/18.0	ETE842	56Y	12.27	38
2.60	3450	208-230	60	10.6-10.0	ETE843	56Y	12.27	38

C-Flange, Premium Energy Efficient, Total Horsepower Rated, Category "J"

THP	RPM	Voltage	Freq	Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
1.25	3450	208-230/115	60	5.9-5.5/11.0	ETE638	56J	10.32	29
1.65	3450	208-230/115	60	7.6-7.2/14.4	ETE654	56J	10.32	30
2.25	3450	208-230/115	60	9.7-9.0/18.0	ETE796	56J	11.32	37
2.60	3450	208-230	60	10.6-10.0	ETE809	56J	11.32	37

Catalog numbers are for competitive comparison purposes only.

Extreme-E® represents our most efficient running, highest performing lines of motors.

