

EZ48® Thru-Bolt Pool and Spa Motors 5.5" Frame Diameter



FEATURES:

- Open Dripproof
- Sealed Ball Bearings
- Class B Insulated
- 300 Series Stainless Steel Shaft
- 50° C Ambient
- 3 O'clock Conduit
- Shaft Thread-3/8-16 UNC 2A RH
- Rigid Base
- Thermally Protected
- 1081 Design
- 3 1/2" Shaft Height

Single Speed - 1.5 Compartment

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
1/2	1.00	3450	115	60	7.5	EZBN23	48Y	8.7	15
3/4	1.00	3450	115	60	10.0	EZBN24	48Y	8.7	17
1.0	1.00	3450	115	60	12.0	EZBN25	48Y	9.3	22
1.5	1.00	3450	115	60	16.0	EZBV35	48Y	9.8	25
1.5	1.00	3450	230/115	60	7.7/15.4	EZBN35	48Y	9.8	25

Two Speed - 1.5 Compartment

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
3/4/.10	1.00	3450/1725	115	60	9.8/3.2	EZBN36	48Y	8.7	17
1.0/.12	1.00	3450/1725	115	60	12.2/3.8	EZBN37	48Y	9.2	22
1.5/.18	1.00	3450/1725	115	60	16.0/4.8	EZBN50	48Y	11.6	25

Rocker Switch Cover Assembly available:

Two Speed - LO-OFF-HI-X2975862300000L

One Speed - ON-OFF-X2975862200000L

Thru-Bolt Spa Circulator Pump Motors 5.5" Frame Diameter

FEATURES:

- Open Dripproof
- Thru Bolt Mount
- Class B Insulated
- Rigid Base
- 50° C Ambient
- 3 O'clock Conduit
- Thermally Protected
- 3 1/2" Shaft Height
- 1081, 1563 & 1795 Design
- Shaft Thread-3/8-16 UNC 2A RH
- Sealed Ball Bearings

Single Speed - Spa Circulator Pump Motors

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
1/15	1.00	1725	115	60	1.3	EV115	48Y	7.25	11.4
1/15	1.00	1725	230	60	0.63	EV230	48Y	7.25	11.7

Catalog numbers are for competitive comparison purposes only.