

Thru Bolt Pool and Spa 6.5" Frame Diameter



FEATURES:

- Open Dripproof
- Thru Bolt Mount
- Class F Insulated
- Class B Temperature Rise
- 1081 & 1563 Design
- Sealed Ball Bearing
- Rigid Base
- Thermally Protected
- 60° C Ambient
- 3 O'clock Conduit
- Premium Energy Efficient Design
- Shaft Thread
3/8-16 UNC-2A

extreme-E Premium Energy Efficient, Single Speed, Switchless Design

HP	SF	THP	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.	Notes
1.5	1.00	1.50	3450	230/115	60	8.8/17.5	TS602	56Y	9.58	28	1
2.0	1.00	2.00	3450	230	60	10.0	TS603	56Y	9.58	31	
2.5	1.00	2.50	3450	230	60	10.5	TS604	56Y	9.58	32	
3.0	1.00	3.00	3450	230	60	12.0	TS605	56Y	10.08	35	
4.0	1.00	4.00	3450	230	60	16.4	TS606	56Y	10.58	39	
5.0	1.00	5.00	3450	230	60	19.5	TS607	56Y	12.58	50	

extreme-E Premium Energy Efficient, Two Speed, Soft Start

HP	SF	THP	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.	Notes
1.5/18	1.00	1.5/18	3450/1725	230	60	8.0/3.0	*TT502	56Y	9.58	31	
2.0/25	1.00	2.0/25	3450/1725	230	60	10.0/3.5	*TT503	56Y	10.08	35	
2.5/33	1.00	2.5/33	3450/1725	230	60	10.5/3.8	*TT504	56Y	10.33	36	
3.0/38	1.00	3.0/38	3450/1725	230	60	12.0/4.4	*TT505	56Y	10.83	41	
4.0/50	1.00	4.0/50	3450/1725	230	60	16.4/4.8	*TT506	56Y	11.58	45	
5.0/63	1.00	5.0/63	3450/1725	230	60	19.5/5.0	*TT507	56Y	12.08	48	



NOTES:
1) Capacitor start design

*California Energy Commission (CEC) Appliance Regulations (Title 20) compliant
Catalog numbers are for competitive comparison purposes only.

extreme-E Extreme-E® represents our most efficient running, highest performing lines of motors.

