

SERVO MOTOR 115UDC306BACAA115190-JSAA

115UDC306BACAA115190-JSAA

HIGH INERTIA MOTOR. 115 PCD EXTENDED FEF, Ø19 x 40mm OUTPUT SHAFT
(motor derated - torque output from motor limited by output shaft diameter)




Definition

Type	Unimotor HD	
Frame Size (mm)	115	
Voltage	U	400 V
Magnet type	D	High Dynamic
Frame Length	C	
Speed (min ⁻¹)	30	3000
Brake	6	Braked
Connection type	B	Power and Signal 90° rotatable (Size 1)
Output shaft	A	With output key
Feedback device code	CA	4096 ppr Incremental encoder (CFS50)
Inertia & thermistor	A - JSAA	High inertia + PTC thermistor
PCD	115	115 (FF 115 / 95)
Shaft Diameter	190	19j6 x 40.0 (torque output from motor limited by output shaft dia)
Fan Box	-	
Insulation class	F	
UL Motor / UL Stator	UL Motor / UL stator	

Nominal characteristics


Motor Ambient Temperature (°C)	40	Drive Fsw (kHz)	12
Motor Stall Torque (N.m)	8.25	Stall Current (A)	5.2
Rated Torque (N.m)	8.25	Nominal Current (A)	5.2
Motor Peak Torque (N.m)	24.8	Kt (Nm/A)	1.6
Rated Power (kW)	2.6	Ke (V/kmin ⁻¹)	98.0
Winding Thermal Time Constant (s)	168	R (ph-ph) (Ohm)	1.2
Number of Poles	10	L (ph-ph) (mH)	12.7
Typical Cogging (N.m)	0.22		
Inertia (kg.cm ²)	14.21	Weight (kg)	12.4
Ingress Protection Level (IP)	IP65		
Brake	Type 6	Static Torque (N.m)	16
Release Time (ms)	110	Backlash (°)	3
Brake Supply Voltage (V)	24	Brake Coil Power (W)	23

Torque / speed graph



Created by: SB / Approved by: DB


SERVO MOTOR 115UDC306BACAA115190-JSAA

Motors ($^{\circ}$ & *mm*)

LB	Total length	336.6
LC	Power connector position	283.8
LA	Flange thickness	10.1
T	Register Length	2.8
N	Register Diameter	95.0
LD	Connector overall height	156.5
P	Flange Square	105.0
S	Fixing Hole Diameter	10.0
M	Fixing hole PCD	115.0
PH	Motor Housing Width	115.0
D	Shaft Diameter	19j6
E	Shaft Length	40.0
GA	Key Height	21.5
GF	Key Length	32.0
G	Key to Shaft End	3.6
F	Key Width	6.0
I	Tapped Hole Thread Size	M6 x 1.0
J	Tapped Hole Depth	17.0
	Mounting Bolt	M8

Motor electrical interface Connectors option:

Feedback device code: CA - 4096 ppr Incremental encoder (CFS50)



- | | |
|------------------|-------------------|
| 1 - Thermistor - | 10 - A |
| 2 - Thermistor + | 11 - Z |
| 3 - | 12 - Z/ |
| 4 - U | 13 - A/ |
| 5 - U/ | 14 - B |
| 6 - V | 15 - B/ |
| 7 - V/ | 16 - Power +5 VDC |
| 8 - W | 17 - 0V |
| 9 - W/ | Body - Screen |

Connection type: B – Power and Signal 90° rotatable (Size 1)

