

COAL LOADER DOWN UNDER RELIES ON CONTROL TECHNIQUES DRIVES

CUSTOMER PROFILE

A new shiploader at Dalrymple Bay Coal Terminal at Hay Point port in Queensland has been fitted with Unidrive SP AC drives. Between 15 and 18 trains are unloaded at the coal terminal daily (approximately 5,500 tonnes per hour) for export, the terminal also serves 14 mines in Queensland.

THE CHALLENGE

The expansion added a new berth and shiploader to the existing 2 berths/2 shiploader combination. The 7,200 tonne per hour shiploader travels alongside a berthed ship on rails on a 200-metre wharf. Reach across the holds is provided by a shuttling head on the boom to ensure even loading and a telescoping loading chute minimises dust generation. The chute directs coal 360° around the hold to make sure the hatch is fully and evenly loaded.

THE SOLUTION

Control Techniques Australia was awarded the contract by Clough Downer JV and designed a scheme where all drives communicate with a PLC via DeviceNet, with encoder feedback giving closed loop motor control, and additional on-board processing. The telescopic chute winch features two 55 kW Unidrives, one for position control, one in regenerative mode, to feed power back to the supply during braking. The boom luffing winch is a 500 kW regenerative system, with three Unidrives power sharing and a further three in regenerative mode.

Travel along the berth is powered by 28 motors controlled in synchronism by four 160 kW Unidrives with four further units giving power regeneration. Using feedback from the drives' software via DeviceNet, the PLC controls the reeling of the cable and hose reels to maintain a constant feed angle on the cable and hose whether reeling in or paying out.

THE BENEFITS

"Despite the size of the coal loader, space for drives cubicles was limited," Ananda Sebastian, Managing Director of Control Techniques Australia Pty in Sydney said, "The client was pleased with our solution based on Unidrive AC drives, and drives and switchgear were mounted back-to-back in specially designed compact cubicles. We had to commission the drives for the boom before it left the dock in the Brisbane River so that the boom could be lowered to pass under the Gateway bridge. Once installed at Dalrymple Bay, we completed the final commissioning, which was completed very quickly to the client's full satisfaction."



KEY BENEFITS

- **COMPACT DRIVES**
- **ENCODER FEEDBACK**
- **ON-BOARD PROCESSING**
- **ENERGY EFFICIENT SYSTEM**

Connect with us at:



www.controltechniques.com



© 2018 Nidec Control Techniques Limited. The information contained in this brochure is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as Nidec Control Techniques Ltd have an ongoing process of development and reserve the right to change the specification of their products without notice.

Nidec Control Techniques Limited. Registered Office: The Gro, Newtown, Powys SY16 3BE. Registered in England and Wales. Company Reg. No. 01236886.