

Plan View @ Lowest Landing
 SCALE : NONE
 (DEPICTING FEATURES AT
 VARIOUS LEVELS)

WALL INSERT BY G.C. -
 SEE NOTES 6 & 7

5" FINISHED SILL PROJECTION
 4" SILL SUPPORT

2 13/16"
 6 5/16"
 7 3/4"
 7'-0 1/2" BACK TO BACK STILES
 7'-3 3/8" D.B.G.
 7'-10 3/8" B.B.G.
 4'-2" TO JACK C/L
 8'-4" MINIMUM CLEAR HOISTWAY
 4'-2" TO JACK C/L

HALL STATION

PIT LIGHT & SWITCH
 (BY ELEC. CONTR.)
 PIT STOP SWITCH
 (BY ELEV. CONTR.)
 PIT LADDER
 (BY G.C.)


JACK, SLING,
 & RAIL C/L

2'-5 1/2" 2'-7 1/2"

5'-1" PLATFORM

2'-11 3/4" TO JACK/RAIL C/L 2'-10 1/4" TO JACK/RAIL C/L

5'-10" CLEAR HOISTWAY

 I N C O R P O R A T E D	
DETAIL: 2500# CAPACITY HYDRAULIC PASSENGER, HOLED (STANDARD IN-GROUND), TWO THRU FOUR STOP, FRONT OPENINGS	
T2502 T2503 T2504	SHEET No. PRELIMT 2 OF 4