



MEASURE OVERALL INSIDE CYLINDER LENGTH AND RECORD BELOW \_\_\_\_\_  
 (DROP A TAPE DOWN THE CYLINDER TO MEASURE THIS DISTANCE)

MINIMUM 4'-0" BELOW PIT CHANNEL EARS OR  
 PIT FLOOR REQUIRED TO BE SENT TO CANTON

(TYPICALLY CYLINDER OUTLET AND PIT CHANNEL EARS ARE REUSED  
 UNLESS THEY ARE FOUND TO BE UNSALABLE.)

CYLINDER PIPE O.D. - \_\_\_\_\_  
 NUMBER OF CYLINDER SECTIONS REQUIRED - \_\_\_\_\_  
 MAXIMUM CYLINDER LENGTH ALLOWABLE - \_\_\_\_\_  
 APPROVED BY - \_\_\_\_\_  
 DATE APPROVED - \_\_\_\_\_

REQUIRED MODIFICATIONS TO EXISTING CYLINDER  
 (IF REQUIRED)

ALL DIMENSIONS ±1/8" UNLESS OTHERWISE NOTED



Ph: 330-833-3600 FAX: 330-833-0229

SURVEY FORM  
 CYLINDER REPAIR

REVISIONS		CANTON ELEVATOR					
ORIG.	9-1-11	BY	LSK	WEIGHT	N/A	DATE	
DATE		BY		STUDY	N/A	BY	
DATE		BY		QTY.	1 JOB	DWG.#	CYLINDER SURV.
DATE		BY		SCALE	NONE	JOB #	