



Motion Control Engineering  
Voice: 916 463 9200  
Fax: 916 463 9201

Element Traction  
Engineering Survey Form

Page 1 of 5

Doc #: 42-FR-0452 B4 (JER144)  
www.nidec-mce.com

Logistics Data

In order to better serve you and meet your schedule, this form must be completed and signed. Timely delivery and trouble-free installation begin with these data forms. Accurate, complete information is essential. Non-response to a question will be defined as meaning that the item does not apply.

**Note:** For any feature, accessory, or provision **NOT** listed, Element Series will not be able to meet the requirements of your application. Please contact your MCE Sales Account Manager for an alternate product price quotation.

Date:	Number of cars:
Job Name: (26 Chars per line)	
Job Location (city and state):	
Contract Date:	
Project Type: <input type="checkbox"/> New construction <input type="checkbox"/> Modernization	
Customer Job #:	PO#:

**Delivery Schedule**

Control	Delivery Date
Car "___"	_____
Car "___"	_____

**Shipping Information**

Contact:		
Phone:	Fax:	
Company name and address:		
City	State	Zip Code
Shipping Requirement:		
Advanced Notice: <input type="checkbox"/> 24 hours <input type="checkbox"/> 48 hours		
Truck w/ Lift Gate: <input type="checkbox"/> Yes <input type="checkbox"/> No		

**Contractor Information** ( Check if same as above)

Contact:		
Phone:	Fax:	
Email:		
Company name and address:		
City	State	Zip Code

**Per state tax laws, it is critical that MCE receive exemption or resale certificates prior to the material being shipped and billed. If the job is a tax-exempt job, send the exemption certificate with this form. If you are a resale customer and have a resale certificate, please make sure that the MCE accounting department has a copy on file.**

**Contact:**

Phone:	Fax:
Cell:	
Email:	
Company name:	
Signature:	

**Elevator Safety Code Compliance**

Accurate information is essential.

<b>North American Compliance:</b> <input type="checkbox"/> U.S. <input type="checkbox"/> Canada
<b>ASME A17.1/B44 Edition:</b> <input type="checkbox"/> 2019 <input type="checkbox"/> 2016 <input type="checkbox"/> 2013 <input type="checkbox"/> 2010 <input type="checkbox"/> 2007 <input type="checkbox"/> 2004 <input type="checkbox"/> 2000
<b>Addenda/Supplements:</b> <input type="checkbox"/> 2008(a) <input type="checkbox"/> 2005(a) <input type="checkbox"/> 2002(a) (None for A17.1-2010 and later) <input type="checkbox"/> 2009(b) <input type="checkbox"/> 2005(S) <input type="checkbox"/> 2003(b)
<input type="checkbox"/> ASME A17.1-1996 Addenda: <input type="checkbox"/> 1997(a) <input type="checkbox"/> 1998(b)
<b>Additional state or local code compliance</b>
<input type="checkbox"/> Chicago Fire Code (select one): <input type="checkbox"/> Current <b>OR</b> <input type="checkbox"/> 2001
<input type="checkbox"/> Denver <input type="checkbox"/> Pressurized hoistway
<input type="checkbox"/> Maryland
<input type="checkbox"/> Massachusetts (2004)
<input type="checkbox"/> Michigan ( <b>NOTE:</b> Detroit <b>not</b> supported.)
<input type="checkbox"/> Nebraska
<input type="checkbox"/> New York City
<input type="checkbox"/> Washington State <input type="checkbox"/> Seattle

**Selective Collective** (Supports single riser installation only)

Simplex     Duplex<sup>1</sup>

**Hoistway Configuration, Speed & Capacity**

Floor Label <sup>2</sup>	Landing #	Floor Height	Car ___ <input type="checkbox"/> FSAE <sup>3</sup>	Car ___ <input type="checkbox"/> FSAE <sup>3</sup>	Lobby Floor	Parking Floor		Fire Service Recall Landing		Car Call Security <input type="checkbox"/> Key Floor Lockout <input type="checkbox"/> Card Reader Dry Contact <sup>4</sup> (24V Contact Rating)	<input type="checkbox"/> Pit Flood Operation	<input type="checkbox"/> EMT Service			
						Main	Alternate	Main	Alternate						
<b>Select floors served:</b>															
	16	O.H.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	15	15-16	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	14	14-15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	13	13-14	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	12	12-13	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	11	11-12	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	10	10-11	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	9	9-10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	8	8-9	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	7	7-8	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	6	6-7	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	5	5-6	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	4	4-5	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	3	3-4	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	2	2-3	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
	1	1-2	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
		Pit	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
Capacity <input type="checkbox"/> lbs <input type="checkbox"/> kg						If no parking floor, car stays at last call answered.		Hoistway Sensor(s) <input type="checkbox"/> Above lowest landing of recall <input type="checkbox"/> At or below lowest landing of recall <input type="checkbox"/> None <input type="checkbox"/> At or below designated level		Key Floor Lockout Switch Location <input type="checkbox"/> COP <input type="checkbox"/> Lobby		Please indicate lowest landing car can serve in an event of a flood.		Please indicate main EMT return floor.	
Car Speed <input type="checkbox"/> fpm <input type="checkbox"/> m/s						<input type="checkbox"/> Park with Doors Open. <input type="checkbox"/> Doors stay open without demand.		Egress floor ___		Card Reader Override Switch Location <input type="checkbox"/> COP <input type="checkbox"/> Lobby <input type="checkbox"/> None					
Total Car Travel: <input type="checkbox"/> ft <input type="checkbox"/> m										<input type="checkbox"/> Independent Service Override					

<sup>1</sup>Only single machine room and single hoistway are supported for duplex applications.

<sup>2</sup>Floor Label note: For CE or E-Motive driver board, floor label should not be more characters than the number of digital PI display characters (888).

<sup>3</sup>Fire Service Access Elevator: If selected, circuitry will be provided to enable hoistway lighting during Fire Service.

<sup>4</sup>Card Reader Dry Contact note: If selected, all floors will be secured by default. However, this can be changed in the controller configuration menu.

**Line Voltage**

**3-Phase AC Line Voltage** (actual measured line voltage)

Symmetrical     Grounded Leg Delta (ISO transformer required)

Choose closest selection below:

208             220             240             440  
 460             480             575             600

60 Hz (standard in U.S.)     50 Hz

Isolation Transformer

Available Fault Current from AC Feed (kA): \_\_\_\_\_

Standard Controller SCCR (Short Circuit Current Rating):

- Up to 50 hp: 5kA
- 51-200 hp: 10kA
- 201-400 hp: 18kA

If the available fault current exceeds these standard values, please notify MCE for a quote.

**Traction Data**
**IMPORTANT:** Only AC geared machine with DC brake supported.

**Machine**     Existing             New  
                    Ring & Worm         Helical

Roping:     1:1                 2:1

Brand: \_\_\_\_\_

Machine Location:     Overhead     Basement  
 (Not supported if Machine is >100ft from controller)

**DC Brake**     Existing             New

Picking: \_\_\_\_\_            Holding: \_\_\_\_\_

Coil Resistance: \_\_\_\_\_    Contact on Brake:     N/O     N/C

**AC Motor**

Brand: \_\_\_\_\_

HP: \_\_\_\_\_                      Voltage: \_\_\_\_\_

FLA: \_\_\_\_\_                      # Poles: \_\_\_\_\_

Sync RPM: \_\_\_\_\_              FL RPM: \_\_\_\_\_

Frequency: \_\_\_\_\_

**Variable Voltage Variable Frequency Drive**

Magnetek HPV-900-S2  
 KEB F5

**Digital Velocity Encoder**

Encoder:     By MCE     By Customer

Cable:         By MCE

Cable Length:     25'     50'     75'     100'(Required)  
 By Customer

**Traction Features**

Auxiliary Battery Power Supply  
 (MCE TAPS) (Provides backup power for your AC controller, with sizing up to 30HP applications)

Suspension-Means Monitoring (req'd for A17.1-2010 and later)

Steel wire ropes ≥ 8mm (Standard)

Steel wire ropes < 8mm\*

Suspension means other than steel wire ropes \*

\* For non-standard suspension means, the customer must provide the Broken Suspension Member (2.20.8.2) or Suspension Member Residual Strength (2.20.8.3) monitoring means, including a normally closed contact.

**Emergency Brake (Sheave brake not supported)**

ASME A17.1-2000/CSA B44-00 or later requires the addition of an emergency brake on all new traction elevators, per 2.19. Also note that some alterations may trigger the requirement to add an emergency brake as well, depending on the Code edition (e.g., change in type of service, operation or motion control; increase in rated load or speed; changing the location of or replacing the driving machine; or replacing the motion controller).

Hollister Whitney Hydraulic Rope Gripper (or equivalent)  
 (Standard 120VAC power supply)

Hollister Whitney Linear Rope Gripper  
 (Standard 120VAC power supply)

**Operating Features**

**Earthquake Service**

**Seismic Switch**     By MCE     By Customer

**Counterweight Derailment Device**     By MCE     By Customer

Alarm Button (required in COP; 2016 or later)

Earthquake Hoistway Scan Switch in COP? (optional for 2016 and later)

**NOTE: A manually reset switch that is positively opened mechanically must be provided at the machine to detect the displacement of the suspension members or the suspension members' retainer.**

**Earthquake Indicators** (2016 and later)

Earthquake Slow Speed (required in COP for EQ Hoistway Scan)

Earthquake Mode (COP)

Seismic Status (adjacent to each inspection station)

Adjacent to controller

Adjacent to car top inspection station

Adjacent to in-car inspection switch

Other inspection stations (list) \_\_\_\_\_

Alarm bell in building audible in each car (activated by Alarm button COP; not powered by controller)

Per car     Per group

Emergency Power Generator

**Simplex**    Resume operation after recovering to closest floor

**Duplex**    Sequentially lowers both cars to lobby. 3-position Emergency power/standby switch (Auto / Car A / Car B) will select which elevator to run.

**Fire Service Operation** (Fire Operation Provided as Standard)

Additional Phase 1 Recall Switch

Nudging during Fire Recall

**Inspection/Access Requirements**

Car Top Inspection Station by MCE (NEMA 1 only)

In-Car (2-position switch)

With Up/Down Buttons

Hoistway Access (2-position switch on COP required)

Top                       Bottom

**Load Weigher**

EMCO Rope Tension Load Weigher (Simplex/Car A)

Number of Ropes     4     5     6     7     8

Roping Diameter:     10mm     1/2"     9/16"     5/8"

EMCO Rope Tension Load Weigher (Car B)

Number of Ropes     4     5     6     7     8

Roping Diameter:     10mm     1/2"     9/16"     5/8"

Discrete Load Weigher Interface

**Recall Switch**

**Car to Lobby Switch**

Recall Landing: \_\_\_\_\_                      Floor Label: \_\_\_\_\_

Park with doors:                       Open     Closed

Location of Switch:                       Car     Hall

**Car to Floor Switch**

Recall Landing: \_\_\_\_\_                      Floor Label: \_\_\_\_\_

Park with doors:                       Open     Closed

Location of Switch:                       Car     Hall

**Car Shut Down Switch**

Recall Landing: \_\_\_\_\_                      Floor Label: \_\_\_\_\_

Park with doors:                       Open     Closed

Location of Switch:                       Car     Hall

**Hoistway**
**IMPORTANT:** Only NEMA 1 hoistway supported on this product. Reduced stroke buffers NOT supported.

**Landing System**

Distance Feedback

LS-EDGE    Tape Length Required (ft): \_\_\_\_\_

Tape Type:     Steel (Std.)     Stainless Steel

LS-RAIL (Not currently available) (Not recommended on systems with slide guides due to wheel slip and contaminant issues)

**EEOC Limit Switch**

Note: Except for final limits, mechanical limits are not required with LS-EDGE.

**Element Traveling Cable** (see page 5 for details)

Cable Length Required (ft): \_\_\_\_\_ (Hang Length Max. 200 ft)

Cable Accessories:     Kellerm Grips

**Automatic Passenger Style Doors**

**IMPORTANT:** Only fully automatic, horizontally sliding, passenger-style doors are supported on this product.

**Built-in:** Door operator interface is built in. The controller can interface with the door operator directly.

**IPC Universal Interface:** Interface with existing operator to open loop. Uses IPC Universal Interface Board.

**SmarTraq Upgrade Kit:** Upgrades existing door operator to closed loop. Comes with drive interface and motor.

**Door Operator**

Manufacturer	Model	Interface
Armor	C4	<input type="checkbox"/> SmarTraq Upgrade Kit
		<input type="checkbox"/> Built-In
ECI	895	<input type="checkbox"/> Built-In
	1000	<input type="checkbox"/> Built-In
	2000	<input type="checkbox"/> Built-In
	VFE2500 (220V only)	<input type="checkbox"/> Built-In
GAL	MOD (220V only)	<input type="checkbox"/> Built-In
	MODHFL (220V only)	<input type="checkbox"/> Built-In
	MODP	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	MOVFR (220V only)	<input type="checkbox"/> Built-In
Haughton	T	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	T1	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	TH	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
MCE	Profile	<input type="checkbox"/> Built-In
	SmarTraq	<input type="checkbox"/> Built-In
Montgomery	MAC PMSSC	<input type="checkbox"/> SmarTraq Upgrade Kit <input type="checkbox"/> IPC Universal Interface
	Old-Style MAC	<input type="checkbox"/> SmarTraq Upgrade Kit
Otis	7300	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	7782	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	6970A - Reactance	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	6970A - Resistance	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	AT400*	<input type="checkbox"/> Built-In
	OVL (Gear Ratio 6:67.1)	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	OVL (Gear Ratio 11:33.1)	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
TKE/Dover	052	<input type="checkbox"/> IPC Universal Interface
	DC-62	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	DC-68	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	HD-70	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	HD-73	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	HD-85	<input type="checkbox"/> SmarTraq Upgrade Kit
	HD-91	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	HD-98	<input type="checkbox"/> SmarTraq Upgrade Kit
	HD-LM	<input type="checkbox"/> Built-In
	MKII	<input type="checkbox"/> IPC Universal Interface
	Type D	<input type="checkbox"/> IPC Universal Interface
Westinghouse	A	<input type="checkbox"/> SmarTraq Upgrade Kit
	AA	<input type="checkbox"/> IPC Universal Interface
	B	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	BB	<input type="checkbox"/> IPC Universal Interface
	BB2	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	E	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	E4A	<input type="checkbox"/> IPC Universal Interface
	EZ	<input type="checkbox"/> SmarTraq Upgrade Kit
	HY	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	MG	<input type="checkbox"/> IPC Universal Interface <input type="checkbox"/> SmarTraq Upgrade Kit
	MS	<input type="checkbox"/> IPC Universal Interface

\*Requires customer supplied DC Power Supply.

**Door Features**

- Door Hold Operation (non-fire operation)
  - Switch
  - Button (default hold time = 120 seconds)
- Infrared detector unit/photo eye
  - Cut-out switch in COP
- Nudging Output†
  - Buzzer only (doors remain open)
  - Reduced closing torque & buzzer
  - Nudging with stuck photo eye

† Buzzers/Lights must be 24VDC

**Fixtures**

- Auxiliary Car Station**
  - Discrete wiring to main COP board.
  - Provide additional serial COP board.

**Call Registration**

- Serial Car Call (standard)
- Serial Hall Call (standard)

**Lanterns & Gongs/Chimes**

- Car Lanterns†
  - Discrete
  - Serial 3-wire
- Hall Lanterns† (Only Serial 3-wire supported)
- Passing Floor Gong†
  - Passing Floor Gong Enable ("S") Button Interface

† Buzzers/Lights must be 24VDC

**Indicators†**

- Call Registration Buzzer
- Door Hold Light
- Egress Floor Gong
- In-Service Light
- Security Light

† Buzzers/Lights must be 24VDC

**Serial Fixture Driver Format** (Built into CPU board in controller)

- CE Electronics 3-Wire Micro Comm
- E-Motive 3-Wire Driver

**Serial Fixture Pre-Wire**

Ship Serial Boards to fixture manufacture for pre-wire:

Contact Person: \_\_\_\_\_

Phone#: (\_\_\_\_) \_\_\_\_ - \_\_\_\_\_

- |   |                                  |                                |
|---|----------------------------------|--------------------------------|
| <input type="checkbox"/> C.E. Electronics           | <input type="checkbox"/> EPCO    | <input type="checkbox"/> Dupar |
| <input type="checkbox"/> Innovation Industries      | <input type="checkbox"/> Monitor | <input type="checkbox"/> Mad   |
| <input type="checkbox"/> ERM                        | <input type="checkbox"/> PTL     |                                |
| <input type="checkbox"/> Elevator Contractor Office |                                  |                                |
| <input type="checkbox"/> Other                      |                                  |                                |

Which boards to be sent?  COP  Hall Station Node

 **Voice annunciation**

- MCE CE 3-wire driver board interface (built into controller)
- Other: \_\_\_\_\_

**Element Traveling Cable**

**Part Number:** 44-03-0048

**Maximum length:** 200 feet

**Overall Diameter:** 1.37 inches (34.7 mm).

**Cable Net Weight:** 946 lbs/1000 ft (1407 kg/km).

**Conductors:** Stranded bare soft drawn copper.

**Insulation:** 60 degrees C, 300 volt rated.

**Shielded Pairs:** 2 twisted 20 AWG conductors, copper braid shield, PVC jacket.


**Braid:** Rayon, 95% coverage of the core.

**Jacket:** 60 degree C PVC with wear-resistant surface. Retards flame, inhibits oxidation, resists effects of sunlight, water, oil, weathering effects, and most solvents and chemicals.

**18 AWG Wires:** 34

**20 AWG Pairs:** 5

**14 AWG Wires:** 6



18 AWG		20 AWG Pair			14 AWG	
Conductor #	Insul Color	Conductor Color	Conductor Print	Jacket Color	Conductor #	Insul Color
SPD1	Blue	Black/White	CANL1/CANH1	Orange	BLK	Black
SPD0	Blue	Black/White	CANL2/CANH2	Red	WHT	White
DZ	Blue	Black/White	T1/T2	Black	GND	Green
+24	Blue	Black/White	SpareA/SpareB	Tan	1	Orange
CDATA	BLUE	Black/White	SpareC/SpareD	Tan	FLO	Lavender
CTEN	Blue				Spare	Tan
INCP	Blue					
ICTU	Blue					
ICTD	Blue					
INCT	Blue					
INA	Blue					
ICEN	Blue					
ICPU	Blue					
ICPD	Blue					
UTL	Orange					
USL1	Orange					
DTL	Orange					
DLS1	Orange					
SAFH	Orange					
SAFC	Orange					
ESC	Orange					
2	Orange					
GS	Orange					
24CTP	Blue					
Wire1 - 10	Tan					

**Caution:** Hoistway and traveler cables support general requirements for most installations. The customer is solely responsible for making certain that the wire count and type, cable attributes, and length are sufficient before ordering product.