

Refrigeration Condenser Fan 5.0" and 5.6" Diameter Open Drip-Proof, Totally Enclosed, Air Over and Open Air Over



APPLICATIONS:

Condenser cooling fan motors to meet manufacturer's requirements for commercial refrigeration units.

FEATURES:

- OEM Direct Replacements
- Single Speed
- Automatic Reset Thermal Overload Protector
- Designed for use with 370V Capacitors
- **Discount Symbol: DS-3HAC**




Figure A




Figure B

5.0" Diameter, 5/16" Diameter Shaft

| HP | RPM | Voltage | Catalog Number | Bearings | Cap. MFD | Amps | Shaft N | Shell XI | Total C | Shaft Dia. | Mount | Ship Wt. | Notes | OEM | List |
|------|------|---------|----------------|----------|----------|------|---------|----------|---------|------------|----------|----------|-------|-----|-------|
| 1/20 | 1500 | 230 | 1775P | SAB | 3.0 | .5 | 3.1 | 3.8 | 6.9 | 5/16" | Hub Ring | 7 | 98 | TE | \$148 |
| 1/15 | 1500 | 230 | 1779P | SAB | 3.0 | .62 | 3.1 | 3.8 | 6.9 | 5/16" | Hub Ring | 8 | 98 | TE | \$154 |

5.6" Permanent Split Capacitor

| HP | RPM | Voltage | Catalog Number | Bearings | Cap. MFD | Amps | Shaft N | Shell XI | Total C | Mount | Ship Wt. | Notes | OEM | List |
|-----|--------|-------------|----------------|----------|----------|---------|---------|----------|---------|-----------|----------|------------------|-----|-------|
| 1/6 | 1550 | 208-230 | 6128 | SAB | 5.0 | 9.0 | 2.5 | 4.1 | 7.6 | Resilient | 17 | 98, 64, H36 | CO | \$263 |
| | 1550 | 208-230 | 1645 | Ball | 3.0 | 1.4 | 2.1 | 3.8 | 6.4 | Stud | 12 | H35 | HU | \$263 |
| | 1550/1 | 460 | 1265 | SAB | 3 | 0.55 | 3.1 | 4.1 | 7.1 | Bracket | 9 | 98 | CO | \$248 |
| 1/5 | 1075 | 208-230 | 1648 | Ball | 4.0 | 2.0 | 2.5 | 4.3 | 7.9 | Stud | 13 | H35 | HU | \$244 |
| | 1075 | 575 | 1093 | Ball | 4.0 | .80 | 2.5 | 4.8 | 8.4 | Stud | 13 | H36 | | \$246 |
| 1/4 | 1550 | 230 | 6124 | SAB | 5.0 | 2.1 | 3.0 | 4.1 | 7.1 | Band | 13 | 64, H36 | CO | \$242 |
| | 1625 | 208-230 | 6129 | SAB | 5.0 | 1.5 | 2.3 | 4.3 | 7.9 | Resilient | 17 | 64, H36 | CO | \$273 |
| | 1625 | 230 | 3042 | Ball | 4.0 | 1.4 | 1.5 | 5.1 | 7.7 | Hub Ring | 12 | 64, H4, H36 | TY | \$239 |
| | 1625 | 230 | 8330 | SAB | 4.0 | 1.9 | 2.2 | 4.3 | 7.7 | 3 Lugs | 12 | 64, 98, H36, H42 | TE | \$241 |
| | 1625 | 380-420/460 | 8331 | SAB | 4.0 | .95 | 2.2 | 4.3 | 7.7 | 3 Lugs | 12 | 98, 64, H36, H42 | TE | \$257 |
| | 1625 | 575 | 1312 | SAB | - | 0.7 | 3.1 | 4.8 | 7.9 | Band | 13 | 64, 98 | | \$250 |
| 1/3 | 1625 | 208-230 | 6127 | SAB | 4.0 | 2.2 | 1.75 | 5.8 | 8.7 | Resilient | 17 | 98, 64, H45 | CO | \$264 |
| | 1625 | 208-230 | 7232 | SAB | 6.0 | 2.9 | 3.7 | 4.6 | 9.3 | Hub Ring | 16 | 64, H35 | HR | \$173 |
| | 1075/2 | 208-230 | 1354 | Ball | - | 2.0 | 3.1 | 4.8 | 8.4 | 3 Lugs | 11 | | | \$239 |
| 1/2 | 1725 | 208-230 | 644 | Ball | 5.0 | 2.7 | 3.5 | 5.1 | 9.1 | Stud | 15 | 98, H18, H36 | HU | \$250 |
| | 1100/1 | 208-230/460 | 4941 | BALL | 12.5 | 2.8/1.5 | 4.5 | 6.9 | 11.4 | Resilient | 16 | - | - | \$350 |

CO = Copeland HU = Hussmann HR = Hill Refrigeration TE = Tecumseh TY = Tyler

Note 64: Capacitor Included
 Note 98: 50/60 Hz
 Note H4: 2-1/4" hub rings
 Note H18: Conduit box

Note H35: Open Air Over
 Note H36: Open Drip-Proof
 Note H42: Shaft Down
 Note H45: Totally Enclosed, Air Over