

RESCUE® EZ13™ Universal ECM Replacement, Direct Drive Blower, 5.6" Diameter, Open Air Over


APPLICATIONS:

Universal high-efficiency ECM designed as a drop-in replacement for OEM constant torque motors.



FEATURES:

- Universal ECM Replacement for Selectech, X13 and EnduraPro
- Available in dual voltage (115/208-230V)
- No Programming required
- Auto-Sensing Rotation (460V version uses reversing plug)
- Uses Equipment's existing connections, for ease of installation
- High Efficiency Design
- Smooth, Quiet Start-Up and Speed Changes
- Potted Electric Module for Superior Moisture Protection
- Quiet Operation
- Belly Band Mounted
- 6000V Surge Protection
- Ball Bearings
- **Discount Symbol: DS-3ECM**



Single Voltage

| HP | RPM | Voltage | Catalog Number | List | Shaft N | Shell XI | Total C | Ship Wt. (lbs) |
|-----|----------------|-----------|----------------|-------|---------|----------|---------|----------------|
| 1/2 | 1050 / VAR SPD | 208-230 V | 56205S | \$393 | 5.5 | 4.0 | 12.1 | 10 |
| 1/2 | 1050 / VAR SPD | 115 V | 56105S | \$393 | 5.5 | 4.0 | 12.1 | 12 |
| 3/4 | 1050 / VAR SPD | 208-230 V | 56207S | \$431 | 5.5 | 4.4 | 12.5 | 14 |
| 3/4 | 1050 / VAR SPD | 115 V | 56107S | \$431 | 5.5 | 4.4 | 12.5 | 14 |
| 1 | 1050 / VAR SPD | 208-230 V | 56210S | \$448 | 5.5 | 4.8 | 12.8 | 18 |
| 1 | 1050 / VAR SPD | 115 V | 56110S | \$448 | 5.5 | 4.8 | 12.8 | 18 |

Dual Voltage

| HP | RPM | Voltage | Catalog Number | List | Shaft N | Shell XI | Total C | Ship Wt. (lbs) |
|-----|----------------|---------------|----------------|-------|---------|----------|---------|----------------|
| 1/2 | 1075 / VAR SPD | 115/208-230 V | 5632 | \$393 | 5.0 | 3.7 | 11.2 | 13 |
| 3/4 | 1075 / VAR SPD | 115/208-230 V | 5642 | \$431 | 5.0 | 4.0 | 11.6 | 12 |
| 1 | 1075 / VAR SPD | 115/208-230 V | 5652 | \$448 | 5.0 | 4.4 | 12.0 | 14 |

460 Volts

| HP | RPM | Voltage | Catalog Number | List | Shaft N | Shell XI | Total C | Ship Wt. (lbs) |
|-----|----------------|---------|----------------|-------|---------|----------|---------|----------------|
| 1/3 | 1050 / VAR SPD | 460 V | 5624 | \$468 | 5.0 | 3.5 | 11.4 | 10 |
| 1/2 | 1050 / VAR SPD | 460 V | 5634 | \$491 | 5.0 | 3.9 | 11.7 | 12 |
| 3/4 | 1050 / VAR SPD | 460 V | 5644 | \$539 | 5.0 | 4.3 | 12.1 | 14 |
| 1 | 1050 / VAR SPD | 460 V | 5654 | \$560 | 5.0 | 4.6 | 12.5 | 16 |

