

RESCUE® PerfectSpeed® ECM Ventilation Motor, With User Interface for Speed Control, 5.6" Diameter, Open Air Over


APPLICATIONS:

ECM with user interface for speed control use in commercial ventilation and other air moving applications.



FEATURES:

- **MOTOR:**
 - Highly Efficient ECM
 - Reversible Rotation
 - 300 RPM minimum speed
 - Tri-Voltage models available
 - Smooth, Quiet Start-Up and Speed Changes
 - Potted Electric Module for Superior Moisture Protection
- **USER INTERFACE:**
 - Can be mounted directly to the motor control or remotely, providing easy access.
 - Powered off any line voltage from 115V-277V no separate transformer required.
 - Adjust motor speed by using the onboard potentiometer.
 - Optional remote 0-10VDC potentiometer (user-supplied)



Rigid Base

HP	RPM	Voltage	Catalog Number	List	Shaft N	Shell XI	Total C	Ship Wt. (lbs)
1 - 3/4	1800 / VAR SPD	115/208-230 V	B8450UI	\$498	4.5	4.8	11.9	17
1 - 3/4	1075 / VAR SPD	115/208-230 V	B8650UI	\$495	4.5	4.8	11.9	17
1/2 - 1/3	1800 / VAR SPD	115/208-230 V	B8430UI	\$472	4.5	4.8	11.4	13
1/2 - 1/3	1250 / VAR SPD	115/208-230 V	B8630UI	\$477	4.5	4.8	11.4	13

Stud or Band Mount

HP	RPM	Voltage	Catalog Number	List	Shaft N	Shell XI	Total C	Ship Wt. (lbs)
1 - 3/4	1800 / VAR SPD	115/208-230-277 V	8452UI	\$725	4.5	4.4	11.5	16
1 - 3/4	1050 / VAR SPD	115/208-230-277 V	8652UI	\$758	4.5	4.8	11.9	16
1/2 - 1/3	1800 / VAR SPD	115/208-230-277 V	8432UI	\$686	4.5	3.7	10.7	12
1/2 - 1/3	1050 / VAR SPD	115/208-230-277 V	8632UI	\$691	4.5	4.0	11.1	12
3/4 - 1/2	1800 / VAR SPD	115/208-230-277 V	8442UI	\$705	4.5	4.0	11.1	14
3/4 - 1/2	1050 / VAR SPD	115/208-230-277 V	8642UI	\$725	4.5	4.4	11.5	14

