

Special Application Close Coupled Pump Three Phase Open Drip Proof (ODP) NEMA[®] Premium Efficient


**NEMA
Premium**
**DE1, DE3,
DE4, DEF4**

APPLICATIONS:

For the specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft. Used in damp, dusty or dirty environments.

FEATURES:

- Class F Insulation, Class B Rise At Service Factor
- Rolled Steel Frame
- Aluminum End Shields 140-250, Cast Iron End Shields 280-320
- Oversized Ball Bearings w/Locked Shaft End Construction
- Premasked Mylar Nameplate (with "CE" Mark)
- F1 Assembly Position
- Regreaseable Bearings 180 Frame & Up, Lifting Provisions 210 Frame & Up
- Double Shielded Bearings
- 40°C Ambient, NEMA[®] Design B Performance On 60 Hertz Sine Wave Power
- "JM" Shaft For Mechanical Seal
- "JM" Shaft on 210 Frame and Smaller; JP Shaft on 250 and 280 Frame

JM Shaft - Footed

| HP | RPM | Voltage | Frame | Catalog Number | List | Discount Symbol | SF | "C" Dim. (inches) | Ship Wt. (lbs) | Full Load Eff. | Full Load Amps | Notes |
|-------|------|-------------|-------|----------------|---------|-----------------|------|-------------------|----------------|----------------|----------------|--------------|
| 3/4 | 1200 | 208-230/460 | 143JM | DJ34P3DM | \$655 | DS-3POP | 1.15 | 15.0 | 30 | 80.0 | 2.8-2.8/1.4 | 03 |
| 1 | 1800 | 200 | 143JM | DJ1P2HM | \$487 | DS-3POP | 1.15 | 15.0 | 30 | 85.5 | 3.6 | |
| | 1800 | 208-230/460 | 143JM | DJ1P2DM | \$487 | DS-3POP | 1.15 | 15.0 | 30 | 85.5 | 3.1-3.1/1.5 | 03 |
| | 1200 | 208-230/460 | 145JM | DJ1P3DM | \$655 | DS-3POP | 1.15 | 15.0 | 35 | 82.5 | 4/4/2002 | 03 |
| 1 1/2 | 3600 | 208-230/460 | 143JM | DJ32E1DM | \$491 | DS-3FPO | 1.15 | 15.0 | 30 | 82.5 | 4.3-4/2 | 03,16,NNP,LA |
| | 3600 | 208-230/460 | 143JM | DJ32P1DM | \$519 | DS-3POP | 1.15 | 15.0 | 30 | 85.5 | 4.2-3.8/1.9 | 03 |
| | 1800 | 200 | 145JM | DJ32P2HM | \$513 | DS-3POP | 1.15 | 15.0 | 35 | 86.5 | 4.8 | |
| | 1800 | 208-230/460 | 145JM | DJ32P2DM | \$513 | DS-3POP | 1.15 | 15.0 | 35 | 86.5 | 4.4-4.1/2.1 | 03 |
| | 1200 | 208-230/460 | 182JM | DJ32P3DM | \$660 | DS-3POP | 1.15 | 16.0 | 50 | 86.5 | 5.2-5.3/2.6 | 03 |
| | 3600 | 208-230/460 | 145JM | DJ2E1DM | \$524 | DS-3FPO | 1.15 | 15.0 | 35 | 84.0 | 5.6-5.1/2.5 | 03,16,NNP,LA |
| 2 | 3600 | 208-230/460 | 145JM | DJ2P1DM | \$567 | DS-3POP | 1.15 | 15.0 | 35 | 85.5 | 5.5-5/2.5 | 03 |
| | 1800 | 200 | 145JM | DJ2P2HM | \$563 | DS-3POP | 1.15 | 15.0 | 35 | 86.5 | 6.3 | |
| | 1800 | 208-230/460 | 145JM | DJ2P2DM | \$563 | DS-3POP | 1.15 | 15.0 | 35 | 86.5 | 5.9-5.6/2.8 | 03 |
| | 1800 | 575 | 145JM | DJ2E2GM | \$482 | DS-3FPO | 1.15 | 15.0 | 37 | 84.0 | 2.4 | NNP,LA |
| | 1800 | 575 | 145JM | DJ2P2GM | \$563 | DS-3POP | 1.15 | 15.0 | 35 | 85.5 | 2.2 | |
| | 1200 | 208-230/460 | 184JM | DJ2P3DM | \$739 | DS-3POP | 1.15 | 16.0 | 60 | 87.5 | 6.4-6.3/3.1 | 03 |
| | 3600 | 208-230/460 | 145JM | DJ3P1DM | \$582 | DS-3POP | 1.15 | 15.0 | 35 | 85.5 | 8.3-7.4/3.7 | 03 |
| | 1800 | 200 | 182JM | DJ3P2HM | \$598 | DS-3POP | 1.15 | 16.0 | 50 | 89.5 | 8.8 | |
| 3 | 1800 | 208-230/460 | 182JM | DJ3P2DM | \$598 | DS-3POP | 1.15 | 16.0 | 50 | 89.5 | 8.3-7.7/3.8 | 03 |
| | 1200 | 208-230/460 | 213JM | DJ3P3DM | \$941 | DS-3POP | 1.15 | 18.0 | 90 | 88.5 | 9.4-8.9/4.4 | 03 |
| | 3600 | 200 | 182JM | DJ5E1HM | \$718 | DS-3FPO | 1.15 | 17.0 | 50 | 85.5 | 14.8 | NNP,LA |
| | 3600 | 200 | 182JM | DJ5P1HM | \$620 | DS-3POP | 1.15 | 16.0 | 50 | 88.5 | 14.1 | |
| 5 | 3600 | 208-230/460 | 182JM | DJ5P1DM | \$620 | DS-3POP | 1.15 | 16.0 | 50 | 87.5 | 13.8-12.5/6.2 | 03 |
| | 1800 | 200 | 184JM | DJ5P2HM | \$645 | DS-3POP | 1.15 | 16.0 | 60 | 89.5 | 14.2 | |
| | 1800 | 208-230/460 | 184JM | DJ5P2DM | \$645 | DS-3POP | 1.15 | 16.0 | 60 | 89.5 | 13.7-12.4/6.2 | 03 |
| | 1800 | 575 | 184JM | DJ5P2GM | \$645 | DS-3POP | 1.15 | 16.0 | 60 | 89.5 | 4.9 | |
| | 1200 | 208-230/460 | 215JM | DJ5P3DM | \$1,234 | DS-3POP | 1.15 | 19.0 | 105 | 89.5 | 15.2-14.5/7.3 | 03 |
| | 3600 | 208-230/460 | 184JM | DJ7P1DM | \$968 | DS-3POP | 1.15 | 16.0 | 60 | 88.5 | 20.3-18.1/9.1 | 03 |
| | 1800 | 200 | 213JM | DJ7P2HM | \$943 | DS-3POP | 1.15 | 18.0 | 90 | 91.0 | 21.4 | |
| 7 1/2 | 1800 | 208-230/460 | 213JM | DJ7P2DM | \$943 | DS-3POP | 1.15 | 18.0 | 90 | 91.0 | 20.2-18.5/9.3 | 03 |
| | 1800 | 575 | 213JM | DJ7P2GM | \$943 | DS-3POP | 1.15 | 18.0 | 90 | 91.0 | 7.3 | |

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note LA Limited Availability
Note NNP Non-NEMA[®] Premium

Note 16 Motors marked 208-230/460 volts may not meet all NEMA (MG-1) performance standards when operated at 208 volts

Special Application Close Coupled Pump Three Phase Open Drip Proof (ODP) NEMA® Premium Efficient



NEMA
Premium

DE1

(continued)

| HP | RPM | Voltage | Frame | Catalog Number | List | Discount Symbol | SF | "C" Dim. (inches) | Ship Wt. (lbs) | Full Load Eff. | Full Load Amps | Notes |
|----|------|-------------|-------|----------------|---------|-----------------|------|-------------------|----------------|----------------|----------------|--------|
| 10 | 3600 | 200 | 213JM | DJ10P1HM | \$1,132 | DS-3POP | 1.15 | 18.0 | 90 | 90.2 | 28 | |
| | 3600 | 208-230/460 | 213JM | DJ10P1DM | \$1,132 | DS-3POP | 1.15 | 18.0 | 90 | 90.2 | 27.1-24.3/12.2 | 03 |
| | 3600 | 575 | 213JM | DJ10E1GM | \$1,076 | DS-3FPO | 1.15 | 18.0 | 113 | 88.5 | 10.2 | NNP,LA |
| | 3600 | 575 | 213JM | DJ10P1GM | \$1,132 | DS-3POP | 1.15 | 18.0 | 90 | 90.2 | 9.7 | |
| | 1800 | 200 | 215JM | DJ10P2HM | \$1,147 | DS-3POP | 1.15 | 19.0 | 105 | 91.7 | 28.1 | |
| | 1800 | 208-230/460 | 215JM | DJ10P2DM | \$1,147 | DS-3POP | 1.15 | 19.0 | 105 | 92.4 | 26.3-23.8/11.9 | 03 |
| 15 | 3600 | 208-230/460 | 215JM | DJ15P1DM | \$1,555 | DS-3POP | 1.15 | 19.0 | 105 | 90.2 | 40-36/18 | 03 |
| | 1800 | 230/460 | 254JM | DJ15P2EM | \$1,712 | DS-3POP | 1.15 | 21.1 | 150 | 93.0 | 37/18.3 | 03 |
| 20 | 3600 | 230/460 | 254JM | DJ20P1EM | \$1,874 | DS-3POP | 1.15 | 21.1 | 150 | 91.7 | 46/23.1 | 03 |
| | 3600 | 575 | 254JM | DJ20E1GM | \$1,611 | DS-3FPO | 1.15 | 24.0 | 170 | 90.2 | 18.9 | NNP,LA |
| | 3600 | 575 | 254JM | DJ20P1GM | \$1,874 | DS-3POP | 1.15 | 21.1 | 150 | 91.0 | 18.7 | |
| | 1800 | 230/460 | 256JM | DJ20P2EM | \$1,970 | DS-3POP | 1.15 | 22.4 | 160 | 93.0 | 47/23.6 | 03 |
| 25 | 3600 | 230/460 | 256JM | DJ25P1EM | \$2,567 | DS-3POP | 1.15 | 22.4 | 160 | 91.7 | 57/28.7 | 03 |
| | 1800 | 208-230/460 | 284JM | DJ25P2DM | \$2,435 | DS-3POP | 1.15 | 26.0 | 225 | 93.6 | 58/29 | 03 |
| 30 | 3600 | 208-230/460 | 284JM | DJ30P1DM | \$2,901 | DS-3POP | 1.15 | 26.0 | 225 | 92.4 | 79-68/34 | 03 |
| | 1800 | 208-230/460 | 286JM | DJ30P2DM | \$2,892 | DS-3POP | 1.15 | 26.0 | 250 | 94.1 | 77-69/34 | 03 |
| 40 | 3600 | 208-230/460 | 286JM | DJ40P1DM | \$3,171 | DS-3POP | 1.15 | 26.0 | 250 | 93.0 | 104-90/45 | 03 |
| | 3600 | 575 | 286JM | DJ40P1GM | \$3,171 | DS-3POP | 1.15 | 26.0 | 250 | 93.0 | 36 | |
| | 1800 | 208-230/460 | 324JM | DJ40P2DM | \$3,178 | DS-3POP | 1.15 | 28.0 | 385 | 94.1 | 102-91/46 | 03 |
| 50 | 3600 | 208-230/460 | 324JM | DJ50P1DM | \$3,567 | DS-3POP | 1.15 | 28.0 | 385 | 93.0 | 130-117/59 | 03 |
| | 1800 | 208-230/460 | 326JM | DJ50P2DM | \$3,725 | DS-3POP | 1.15 | 28.0 | 460 | 94.5 | 126-113/56 | 03 |
| 60 | 3600 | 208-230/460 | 326JM | DJ60P1DM | \$4,916 | DS-3POP | 1.15 | 28.0 | 460 | 93.6 | 152-134/67 | 03 |

JM Shaft - Footless

| HP | RPM | Voltage | Frame | Catalog Number | List | Discount Symbol | SF | "C" Dim. (inches) | Ship Wt. (lbs) | Full Load Eff. | Full Load Amps | Notes |
|-------|------|-------------|-------|----------------|---------|-----------------|------|-------------------|----------------|----------------|----------------|-------|
| 1 | 1800 | 208-230/460 | 143JM | DJ1P2DU | \$570 | DS-3POV | 1.15 | 16.0 | 30 | 85.5 | 3.2-3.1/1.6 | 03 |
| 1 1/2 | 3600 | 208-230/460 | 143JM | DJ32P1DU | \$609 | DS-3POV | 1.15 | 16.0 | 30 | 85.5 | 4.2-3.8/1.9 | 03 |
| | 1800 | 208-230/460 | 145JM | DJ32P2DU | \$581 | DS-3POV | 1.15 | 16.0 | 35 | 86.5 | 4.4-4.2/2.1 | 03 |
| 2 | 1800 | 208-230/460 | 145JM | DJ2P2DU | \$642 | DS-3POV | 1.15 | 16.0 | 35 | 86.5 | 5.9-5.6/2.8 | 03 |
| 3 | 1800 | 208-230/460 | 182JM | DJ3P2DU | \$758 | DS-3POV | 1.15 | 17.0 | 50 | 89.5 | 8.3-7.7/3.8 | 03 |
| 5 | 1800 | 208-230/460 | 184JM | DJ5P2DU | \$898 | DS-3POV | 1.15 | 17.0 | 82 | 89.5 | 13.7-12.4/6.2 | 03 |
| 7 1/2 | 1800 | 208-230/460 | 213JM | DJ7P2DU | \$1,188 | DS-3POV | 1.15 | 19.0 | 90 | 91.0 | 20.2-18.5/9.3 | 03 |
| 10 | 3600 | 208-230/460 | 213JM | DJ10P1DU | \$1,420 | DS-3POV | 1.15 | 19.0 | 90 | 90.2 | 27.1-24.3/12.2 | 03 |
| | 1800 | 208-230/460 | 215JM | DJ10P2DU | \$1,400 | DS-3POV | 1.15 | 19.0 | 105 | 91.7 | 26.3-23.8/11.9 | 03 |
| 15 | 3600 | 208-230/460 | 215JM | DJ15P1DU | \$1,809 | DS-3POV | 1.15 | 19.0 | 105 | 90.2 | 40-36/18 | 03 |
| | 1800 | 230/460 | 254JM | DJ15P2EU | \$2,055 | DS-3POV | 1.15 | 21.9 | 150 | 93.0 | 37/18.3 | |
| 20 | 3600 | 230/460 | 254JM | DJ20P1EU | \$2,249 | DS-3POV | 1.15 | 25.5 | 150 | 91.7 | 46/23.1 | 03 |

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note LA Limited Availability

Note NNP Non-NEMA® Premium

Special Application Close Coupled Pump Three Phase Open Drip Proof (ODP) NEMA® Premium Efficient


NEMA
Premium

DE1

(continued)

JP Shaft - Footed

| HP | RPM | Voltage | Frame | Catalog Number | List | Discount Symbol | SF | "C" Dim. (inches) | Ship Wt. (lbs) | Full Load Eff. | Full Load Amps | Notes |
|-------|------|-------------|-------|----------------|---------|-----------------|------|-------------------|----------------|----------------|----------------|--------------|
| 1 | 1800 | 208-230/460 | 143JP | DJ1E2DP | \$455 | DS-3FPO | 1.15 | 18.0 | 32 | 82.5 | 3.1-3/1.5 | 03,16,NNP,LA |
| | 1800 | 208-230/460 | 143JP | DJ1P2DP | \$487 | DS-3POP | 1.15 | 18.0 | 30 | 85.5 | 3.2-3.1/1.6 | 03 |
| 1 1/2 | 1800 | 208-230/460 | 145JP | DJ32P2DP | \$513 | DS-3POP | 1.15 | 18.0 | 35 | 86.5 | 4.4-4.2/2.1 | 03 |
| | 1800 | 208-230/460 | 145JP | DJ2P2DP | \$563 | DS-3POP | 1.15 | 18.0 | 35 | 86.5 | 5.9-5.6/2.8 | 03 |
| 2 | 1800 | 208-230/460 | 182JP | DJ3P2DP | \$598 | DS-3POP | 1.15 | 19.0 | 50 | 89.5 | 8.3-7.7/3.8 | 03 |
| 3 | 1800 | 208-230/460 | 184JP | DJ5P2DP | \$645 | DS-3POP | 1.15 | 19.0 | 60 | 89.5 | 13.7-12.4/6.2 | 03 |
| | 1800 | 208-230/460 | 213JP | DJ7P2DP | \$943 | DS-3POP | 1.15 | 22.0 | 90 | 91.0 | 20.2-18.5/9.3 | 03 |
| 5 | 1200 | 230/460 | 254JP | DJ7P3EP | \$1,565 | DS-3POP | 1.15 | 24.0 | 150 | 91.0 | 18.9/9.5 | 03 |
| 7 1/2 | 3600 | 208-230/460 | 213JP | DJ10P1DP | \$1,132 | DS-3POP | 1.15 | 22.0 | 90 | 90.2 | 27.1-24.3/12.2 | 03 |
| | 1800 | 208-230/460 | 215JP | DJ10P2DP | \$1,147 | DS-3POP | 1.15 | 23.0 | 105 | 91.7 | 26.3-23.8/11.9 | 03 |
| 10 | 1200 | 230/460 | 256JP | DJ10P3EP | \$2,036 | DS-3POP | 1.15 | 25.3 | 160 | 91.7 | 25/12.5 | 03 |
| | 3600 | 200 | 215JP | DJ15P1HP | \$1,555 | DS-3POP | 1.15 | 23.0 | 105 | 90.2 | 41 | |
| | 3600 | 208-230/460 | 215JP | DJ15P1DP | \$1,555 | DS-3POP | 1.15 | 23.0 | 105 | 90.2 | 40-36/18 | 03 |
| | 1800 | 200 | 254JP | DJ15P2HP | \$1,569 | DS-3POP | 1.15 | 27.4 | 150 | 93.0 | 42 | |
| 15 | 1800 | 230/460 | 254JP | DJ15P2EP | \$1,569 | DS-3POP | 1.15 | 24.0 | 150 | 93.0 | 37/18.3 | 03 |
| | 3600 | 230/460 | 254JP | DJ20P1EP | \$1,882 | DS-3POP | 1.15 | 24.0 | 150 | 91.7 | 46/23.1 | 03 |
| | 3600 | 200 | 254JP | DJ20P1HP | \$1,882 | DS-3POP | 1.15 | 24.0 | 150 | 91.7 | 53 | |
| | 3600 | 208-230/460 | 254JP | DJ20P1DP | \$1,882 | DS-3POP | 1.15 | 24.0 | 150 | 91.7 | 53 | |
| 20 | 3600 | 208-230/460 | 254JP | DJ20E1DP | \$1,611 | DS-3FPO | 1.15 | 27.0 | 198 | 90.2 | 54-47/23.6 | 03,16,NNP,LA |
| | 3600 | 575 | 254JP | DJ20E1GP | \$1,611 | DS-3FPO | 1.15 | 27.0 | 195 | 90.2 | 18.9 | NNP,LA |
| | 1800 | 230/460 | 256JP | DJ20P2EP | \$2,012 | DS-3POP | 1.15 | 25.3 | 160 | 93.0 | 47/23.6 | 03 |
| | 1800 | 200 | 256JP | DJ20P2HP | \$2,012 | DS-3POP | 1.15 | 25.3 | 160 | 93.0 | 54 | |
| | 3600 | 230/460 | 256JP | DJ25P1EP | \$2,461 | DS-3POP | 1.15 | 25.3 | 160 | 91.7 | 57/28.7 | 03 |
| 25 | 3600 | 200 | 256JP | DJ25P1HP | \$2,461 | DS-3POP | 1.15 | 25.3 | 160 | 91.7 | 67 | |
| | 3600 | 208-230/460 | 256JP | DJ25E1DP | \$2,094 | DS-3FPO | 1.15 | 28.0 | 210 | 91.0 | 66-58/29 | 03,16,NNP,LA |
| | 1800 | 208-230/460 | 284JP | DJ25P2DP | \$2,435 | DS-3POP | 1.15 | 29.0 | 225 | 93.6 | 64-58/29.2 | 03,06 |
| | 1800 | 200 | 284JP | DJ25P2HP | \$2,435 | DS-3POP | 1.15 | 29.0 | 225 | 93.6 | 67 | |
| | 1800 | 575 | 284JP | DJ25E2GP | \$2,406 | DS-3FPO | 1.15 | 29.0 | 213 | 91.7 | 24.4 | NNP,LA |
| | 1800 | 575 | 284JP | DJ25P2GP | \$2,435 | DS-3POP | 1.15 | 29.0 | 225 | 93.6 | 23.1 | |
| | 3600 | 208-230/460 | 284JP | DJ30P1DP | \$2,901 | DS-3POP | 1.15 | 29.0 | 225 | 92.4 | 79-68/34 | 03 |
| 30 | 1800 | 575 | 284JP | DJ25P2GP | \$2,435 | DS-3POP | 1.15 | 29.0 | 225 | 93.6 | 23.1 | |
| | 3600 | 208-230/460 | 284JP | DJ30P1DP | \$2,901 | DS-3POP | 1.15 | 29.0 | 225 | 92.4 | 79-68/34 | 03 |
| 40 | 1800 | 208-230/460 | 286JP | DJ30P2DP | \$2,892 | DS-3POP | 1.15 | 29.0 | 250 | 94.1 | 77-69/34 | 03 |
| | 3600 | 208-230/460 | 286JP | DJ40P1DP | \$3,171 | DS-3POP | 1.15 | 29.0 | 250 | 93.0 | 104-90/45 | 03 |
| | 3600 | 575 | 286JP | DJ40E1GP | \$3,512 | DS-3FPO | 1.15 | 29.0 | 320 | 93.0 | 36 | NNP,LA |
| | 3600 | 575 | 286JP | DJ40P1GP | \$3,171 | DS-3POP | 1.15 | 29.0 | 250 | 93.0 | 36 | |
| | 1800 | 208-230/460 | 324JP | DJ40P2DP | \$3,178 | DS-3POP | 1.15 | 30.0 | 454 | 94.1 | 102-91/46 | 03 |
| 50 | 3600 | 208-230/460 | 324JP | DJ50P1DP | \$3,567 | DS-3POP | 1.15 | 30.0 | 454 | 93.0 | 130-117/59 | 03 |
| | 1800 | 208-230/460 | 326JP | DJ50P2DP | \$3,725 | DS-3POP | 1.15 | 30.0 | 454 | 94.5 | 126-113/56 | 03 |
| 60 | 3600 | 208-230/460 | 326JP | DJ60P1DP | \$4,915 | DS-3POP | 1.15 | 30.0 | 460 | 93.6 | 152-134/67 | 03 |

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 06 Dual voltage ratings, Part Winding Start on low voltage only

Note 16 Motors marked 208-230/460 volts may not meet all NEMA (MG-1) performance standards when operated at 208 volts

Note LA Limited Availability

Note NNP Non-NEMA® Premium

Special Application Close Coupled Pump Three Phase Open Drip Proof (ODP) NEMA[®] Premium Efficient



**NEMA
Premium**

DE1

(continued)

Westcoast Shaft - Footed

| HP | RPM | Voltage | Frame | Catalog Number | List | Discount Symbol | SF | "C" Dim. (inches) | Ship Wt. (lbs) | NEMA Nom. Eff. | Full Load Amps | Notes |
|-------|------|-------------|--------|----------------|---------|-----------------|------|-------------------|----------------|----------------|----------------|-------|
| 7 1/2 | 1800 | 208-230/460 | 213TCZ | DJ7P2DJ | \$943 | DS-3POP | 1.15 | 21.0 | 90 | 91.0 | 20.2-18.5/9.3 | 03 |
| 10 | 3600 | 208-230/460 | 213TCZ | DJ10P1DJ | \$1,132 | DS-3POP | 1.15 | 21.0 | 90 | 90.2 | 27.1-24.3/12.2 | 03 |
| | 1800 | 208-230/460 | 215TCZ | DJ10P2DJ | \$1,147 | DS-3POP | 1.15 | 22.0 | 105 | 91.7 | 26.3-23.8/11.9 | 03 |
| 15 | 3600 | 208-230/460 | 215TCZ | DJ15P1DJ | \$1,555 | DS-3POP | 1.15 | 22.0 | 105 | 90.2 | 40-36/18 | 03 |

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

BRAKEMOTORS
 GENERAL PURPOSE SINGLE PHASE
 HVAC
 WASHDOWN
 AGRICULTURE
 COMMERCIAL PUMP MOTORS
 CLOSE COUPLED PUMP MOTORS
 FIRE PUMP MOTORS
 POOL & SPA MOTORS
 RESIDENTIAL WATER PUMP
 ELEVATOR GATE & DOOR