

# Special Application Close Coupled Pump Three Phase Totally Enclosed Fan Cooled (TEFC) Premium Efficient



UT4

## APPLICATIONS:

For the specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft.  
Used in damp, dusty or dirty environments.

## FEATURES:

- Class F Insulation, Class B Rise At Full Load On 60 Hertz Sine Wave Power
- Cast Iron Frame 280 & Up, Aluminum 180-250, Rolled Steel 140
- Cast Iron End Brackets 280 & Up, 250 Frame and Lower Has Aluminum With Steel Bearing Inserts
- 40°C Ambient, NEMA®1 Design B Performance On 60 Hertz Sine Wave Power

- Regreasable Shaft End Bearing 180 Frame & Up
- Double Shielded Bearings
- Removable Base (180 - 250 Frame)
- Lifting Provisions 180 Frame & Up
- "JM" Shaft For Mechanical Seal
- "CE" Mark On Nameplate
- Conversion Kits: Canopy Kits

## JM Shaft For Mechanical Seal

| HP    | RPM  | Voltage     | Frame | Catalog Number | List    | Discount Symbol | SF   | "C" Dim. (inches) | Ship Wt (lbs) | Full Load Eff. | Full Load Amps | Notes |
|-------|------|-------------|-------|----------------|---------|-----------------|------|-------------------|---------------|----------------|----------------|-------|
| 1     | 3600 | 230/460     | 143JM | UJ1P1BM        | \$529   | DS-3PT          | 1.25 | 14.3              | 30            | 81.5           | 1.4            |       |
|       | 3600 | 575         | 143JM | UJ1P1GM        | \$529   | DS-3PT          | 1.25 | 14.3              | 30            | 81.5           | 1.1            |       |
|       | 1800 | 208-230/460 | 143JM | UJ1P2DM        | \$518   | DS-3PT          | 1.25 | 15.3              | 30            | 85.5           | 3.1-3/1.5      | 03    |
|       | 1800 | 575         | 143JM | UJ1P2GM        | \$518   | DS-3PT          | 1.25 | 15.3              | 30            | 85.5           | 1.1            |       |
| 1 1/2 | 3600 | 208-230/460 | 143JM | UJ32P1DM       | \$584   | DS-3PT          | 1.25 | 15.3              | 30            | 84.0           | 4.1-3.8/1.9    | 03    |
|       | 3600 | 230/460     | 143JM | UJ32P1BM       | \$584   | DS-3PT          | 1.25 | 14.3              | 30            | 84.0           | 3.9/1.9        | LA    |
|       | 3600 | 575         | 143JM | UJ32P1GM       | \$584   | DS-3PT          | 1.25 | 14.3              | 30            | 84.0           | 1.6            |       |
|       | 1800 | 208-230/460 | 145JM | UJ32P2DM       | \$565   | DS-3PT          | 1.25 | 15.3              | 35            | 86.5           | 4.5-4.3/2.1    | 03    |
|       | 1800 | 575         | 145JM | UJ32P2GM       | \$565   | DS-3PT          | 1.25 | 14.3              | 30            | 86.5           | 1.7            |       |
| 2     | 3600 | 208-230/460 | 145JM | UJ2P1DM        | \$622   | DS-3PT          | 1.25 | 15.3              | 35            | 86.5           | 5.4-4.9/2.5    | 03    |
|       | 3600 | 575         | 145JM | UJ2P1GM        | \$622   | DS-3PT          | 1.25 | 14.3              | 42            | 86.5           | 2              |       |
|       | 1800 | 208-230/460 | 145JM | UJ2P2DM        | \$611   | DS-3PT          | 1.25 | 15.3              | 35            | 86.5           | 5.9-5.7/2.8    | 03    |
|       | 1800 | 575         | 145JM | UJ2P2GM        | \$611   | DS-3PT          | 1.25 | 14.3              | 35            | 86.5           | 2.3            |       |
| 3     | 3600 | 208-230/460 | 182JM | UJ3P1DM        | \$886   | DS-3PT          | 1.25 | 17.8              | 60            | 87.5           | 8.4-7.8/3.9    | 03    |
|       | 3600 | 208-230/460 | 145JM | UJ3P1DFM       | \$738   | DS-3PT          | 1.25 | 15.3              | 35            | 86.5           | 8.1-7.2/3.6    | 03,14 |
|       | 3600 | 575         | 145JM | UJ3P1GFM       | \$738   | DS-3PT          | 1.25 | 15.3              | 35            | 86.5           | 2.9            | 14    |
|       | 3600 | 575         | 182JM | UJ3P1GM        | \$886   | DS-3PT          | 1.25 | 17.8              | 100           | 87.5           | 3.1            |       |
|       | 1800 | 208-230/460 | 182JM | UJ3P2DM        | \$795   | DS-3PT          | 1.25 | 17.8              | 60            | 89.5           | 8.4-7.8/3.9    | 03    |
|       | 1800 | 575         | 182JM | UJ3P2GM        | \$795   | DS-3PT          | 1.25 | 17.8              | 60            | 89.5           | 3.1            |       |
| 5     | 3600 | 208-230/460 | 184JM | UJ5P1DM        | \$1,088 | DS-3PT          | 1.25 | 17.8              | 70            | 88.5           | 13.4-12.2/6.1  | 03    |
|       | 3600 | 575         | 184JM | UJ5P1GM        | \$1,088 | DS-3PT          | 1.25 | 17.8              | 100           | 88.5           | 4.9            |       |
|       | 1800 | 208-230/460 | 184JM | UJ5P2DM        | \$908   | DS-3PT          | 1.25 | 17.8              | 70            | 90.2           | 13.6-12.3/6.2  | 03    |
|       | 1800 | 575         | 184JM | UJ5P2GM        | \$908   | DS-3PT          | 1.25 | 17.8              | 70            | 89.5           | 5              |       |
| 7 1/2 | 3600 | 208-230/460 | 184JM | UJ7P1DFM       | \$1,213 | DS-3PT          | 1.25 | 17.8              | 70            | 90.2           | 19.8-18.9/9.4  | 03,14 |
|       | 3600 | 208-230/460 | 213JM | UJ7P1DM        | \$1,345 | DS-3PT          | 1.25 | 19.9              | 105           | 91.0           | 19.9-17.8/8.9  | 03    |
|       | 3600 | 575         | 184JM | UJ7P1GFM       | \$1,213 | DS-3PT          | 1.25 | 17.8              | 70            | 89.5           | 7.1            | 14    |
|       | 3600 | 575         | 213JM | UJ7P1GM        | \$1,345 | DS-3PT          | 1.25 | 19.8              | 240           | 91.0           | 7.1            |       |
|       | 1800 | 208-230/460 | 213JM | UJ7P2DM        | \$1,228 | DS-3PT          | 1.25 | 19.9              | 105           | 91.7           | 20.0-18.2/9.1  | 03    |
|       | 1800 | 575         | 213JM | UJ7P2GM        | \$1,228 | DS-3PT          | 1.25 | 19.9              | 105           | 91.7           | 7.2            |       |
| 10    | 3600 | 208-230/460 | 215JM | UJ10P1DM       | \$1,556 | DS-3PT          | 1.25 | 19.9              | 120           | 91.0           | 26.4-23.5/11.7 | 03    |
|       | 3600 | 575         | 215JM | UJ10P1GM       | \$1,556 | DS-3PT          | 1.25 | 21.4              | 166           | 91.0           | 9.4            |       |
|       | 1800 | 208-230/460 | 215JM | UJ10P2DM       | \$1,458 | DS-3PT          | 1.25 | 21.4              | 120           | 91.7           | 26.5-23.9/12   | 03    |
|       | 1800 | 575         | 215JM | UJ10P2GM       | \$1,458 | DS-3PT          | 1.25 | 21.4              | 120           | 91.7           | 9.6            |       |
| 15    | 3600 | 208-230/460 | 215JM | UJ15P1DFM      | \$1,801 | DS-3PT          | 1.25 | 21.4              | 120           | 91.0           | 39-36/18       | 03,14 |
|       | 3600 | 208-230/460 | 254JM | UJ15P1DM       | \$2,239 | DS-3PT          | 1.25 | 25.4              | 180           | 91.0           | 39-35/17.7     | 03,14 |
|       | 3600 | 575         | 215JM | UJ15P1GFM      | \$1,801 | DS-3PT          | 1.25 | 21.4              | 120           | 91.7           | 14.4           | 14    |
|       | 3600 | 575         | 254JM | UJ15P1GM       | \$2,239 | DS-3PT          | 1.25 | 25.4              | 180           | 91.0           | 14.1           |       |
|       | 1800 | 208-230/460 | 254JM | UJ15P2DM       | \$2,131 | DS-3PT          | 1.25 | 25.4              | 180           | 92.4           | 40-37/18.4     | 03    |
|       | 1800 | 575         | 254JM | UJ15P2GM       | \$2,131 | DS-3PT          | 1.25 | 25.4              | 180           | 92.4           | 14.6           |       |
| 20    | 3600 | 208-230/460 | 256JM | UJ20P1DM       | \$2,730 | DS-3PT          | 1.25 | 27.1              | 230           | 91.7           | 51-46/23       | 03,14 |
|       | 3600 | 575         | 256JM | UJ20P1GM       | \$2,730 | DS-3PT          | 1.25 | 27.1              | 230           | 91.0           | 18.5           |       |

Note 03 660/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz; 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 14 NEMA®T Design A

## Special Application Close Coupled Pump Three Phase Totally Enclosed Fan Cooled (TEFC) NEMA Premium Efficient



UT4

### UTE4 (continued)

| HP | RPM  | Voltage     | Frame | Catalog Number | List    | Discount Symbol | SF   | "C" Dim. (inches) | Ship Wt (lbs) | Full Load Eff. | Full Load Amps | Notes |
|----|------|-------------|-------|----------------|---------|-----------------|------|-------------------|---------------|----------------|----------------|-------|
| 20 | 1800 | 208-230/460 | 256JM | UJ20P2DM       | \$2,463 | DS-3PT          | 1.25 | 27.1              | 230           | 93.0           | 53-47/23.5     | 03    |
|    | 1800 | 575         | 256JM | UJ20P2GM       | \$2,463 | DS-3PT          | 1.25 | 27.1              | 230           | 93.0           | 19             |       |
| 25 | 3600 | 208-230/460 | 284JM | UJ25P1DM       | \$3,595 | DS-3PT          | 1.25 | 29.1              | 280           | 91.7           | 65.0-57.0/28.4 | 03,14 |
|    | 3600 | 208-230/460 | 256JM | UJ25P1DFM      | \$3,235 | DS-3PT          | 1.15 | 27.1              | 230           | 91.7           | 64-57/28.3     | 03,14 |
|    | 3600 | 575         | 256JM | UJ25P1GFM      | \$3,235 | DS-3PT          | 1.15 | 27.1              | 230           | 91.7           | 22.6           | 14    |
|    | 3600 | 575         | 284JM | HJ25P1GM       | \$3,595 | DS-3PT          | 1.15 | 27.9              | 380           | 91.7           | 23             |       |
|    | 1800 | 208-230/460 | 284JM | UJ25P2DM       | \$3,237 | DS-3PT          | 1.25 | 29.1              | 280           | 93.6           | 65-59/29.3     | 03    |
|    | 1800 | 575         | 284JM | HJ25P2GM       | \$3,237 | DS-3PT          | 1.15 | 27.9              | 380           | 93.6           | 23             |       |
| 30 | 3600 | 460         | 286JM | HJ30P1BM       | \$4,383 | DS-3PT          | 1.15 | 27.9              | 275           | 91.7           | 69/34          |       |
|    | 3600 | 575         | 286JM | HJ30P1GM       | \$4,383 | DS-3PT          | 1.15 | 27.9              | 410           | 91.7           | 27.6           |       |
|    | 1800 | 208-230/460 | 286JM | UJ30P2DM       | \$3,666 | DS-3PT          | 1.25 | 29.1              | 300           | 93.6           | 78.0-70.0/35.0 | 03    |
|    | 1800 | 575         | 286JM | HJ30P2GM       | \$3,666 | DS-3PT          | 1.15 | 27.9              | 410           | 93.6           | 27.6           |       |

### JP Shaft For Packing Seal

| HP    | RPM  | Voltage     | Frame | Catalog Number | List    | Discount Symbol | SF   | "C" Dim. (inches) | Ship Wt (lbs) | Full Load Eff. | Full Load Amps | Notes |
|-------|------|-------------|-------|----------------|---------|-----------------|------|-------------------|---------------|----------------|----------------|-------|
| 1     | 1800 | 208-230/460 | 143JP | UJ1P2DP        | \$518   | DS-3PT          | 1.25 | 18.3              | 30            | 85.5           | 3.1-3/1.5      | 03    |
|       | 1800 | 575         | 143JP | UJ1P2GP        | \$518   | DS-3PT          | 1.25 | 17.3              | 30            | 85.5           | 1.1            |       |
| 1 1/2 | 1800 | 208-230/460 | 145JP | UJ3P2DP        | \$565   | DS-3PT          | 1.25 | 18.3              | 35            | 86.5           | 4.5-4.3/2.1    | 03    |
|       | 1800 | 575         | 145JP | UJ3P2GP        | \$565   | DS-3PT          | 1.25 | 17.3              | 30            | 86.5           | 1.7            |       |
| 2     | 3600 | 208-230/460 | 145JP | UJ2P1DP        | \$622   | DS-3PT          | 1.25 | 18.3              | 35            | 86.5           | 5.4-4.9/2.5    | 03    |
|       | 1800 | 208-230/460 | 145JP | UJ2P2DP        | \$611   | DS-3PT          | 1.25 | 18.3              | 35            | 86.5           | 5.9-5.7/2.8    | 03    |
|       | 1800 | 575         | 145JP | UJ2P2GP        | \$611   | DS-3PT          | 1.25 | 17.3              | 35            | 86.5           | 2.2            |       |
| 3     | 3600 | 208-230/460 | 145JP | UJ3P1DFP       | \$738   | DS-3PT          | 1.25 | 18.3              | 35            | 86.5           | 8.1-7.2/3.6    | 03,14 |
|       | 3600 | 208-230/460 | 182JP | UJ3P1DP        | \$886   | DS-3PT          | 1.25 | 20.9              | 60            | 87.5           | 8.4-7.8/3.9    | 03    |
|       | 1800 | 208-230/460 | 182JP | UJ3P2DP        | \$795   | DS-3PT          | 1.25 | 20.9              | 60            | 89.5           | 8.4-7.8/3.9    | 03    |
|       | 1800 | 575         | 182JP | UJ3P2GP        | \$795   | DS-3PT          | 1.25 | 20.9              | 60            | 89.5           | 3.1            |       |
| 5     | 3600 | 208-230/460 | 184JP | UJ5P1DP        | \$1,088 | DS-3PT          | 1.25 | 20.9              | 70            | 88.5           | 13.4-12.2/6.1  | 03    |
|       | 1800 | 208-230/460 | 184JP | UJ5P2DP        | \$908   | DS-3PT          | 1.25 | 21.6              | 70            | 90.2           | 13.6-12.3/6.2  | 03    |
|       | 1800 | 575         | 184JP | UJ5P2GP        | \$908   | DS-3PT          | 1.25 | 20.9              | 70            | 89.5           | 5              |       |
| 7 1/2 | 3600 | 208-230/460 | 184JP | UJ7P1DFP       | \$1,210 | DS-3PT          | 1.25 | 20.9              | 70            | 90.2           | 19.8-18.9/9.4  | 03,14 |
|       | 3600 | 208-230/460 | 213JP | UJ7P1DP        | \$1,345 | DS-3PT          | 1.25 | 23.8              | 105           | 91.0           | 19.9-17.8/8.9  | 03    |
|       | 1800 | 208-230/460 | 213JP | UJ7P2DP        | \$1,228 | DS-3PT          | 1.25 | 23.8              | 105           | 91.7           | 20-18.2/9.1    | 03    |
|       | 1800 | 575         | 213JP | UJ7P2GP        | \$1,228 | DS-3PT          | 1.25 | 23.8              | 105           | 91.7           | 7.2            |       |
| 10    | 3600 | 208-230/460 | 215JP | UJ10P1DP       | \$1,556 | DS-3PT          | 1.25 | 25.3              | 120           | 91.0           | 26.4-23.5/11.7 | 03    |
|       | 1800 | 208-230/460 | 215JP | UJ10P2DP       | \$1,458 | DS-3PT          | 1.25 | 25.3              | 120           | 91.7           | 26.5-23.9/12   | 03    |
|       | 1800 | 575         | 215JP | UJ10P2GP       | \$1,458 | DS-3PT          | 1.25 | 25.3              | 120           | 91.7           | 9.6            |       |
| 15    | 3600 | 208-230/460 | 215JP | UJ15P1DFP      | \$1,801 | DS-3PT          | 1.25 | 25.3              | 120           | 91.0           | 39-36/18       | 03,14 |
|       | 3600 | 208-230/460 | 254JP | UJ15P1DP       | \$2,239 | DS-3PT          | 1.25 | 28.3              | 180           | 91.0           | 39-35/17.7     | 03,14 |
|       | 1800 | 208-230/460 | 254JP | UJ15P2DP       | \$2,131 | DS-3PT          | 1.25 | 28.3              | 180           | 92.4           | 40-37/18.4     | 03    |
|       | 1800 | 575         | 254JP | UJ15P2GP       | \$2,131 | DS-3PT          | 1.25 | 28.3              | 180           | 92.4           | 14.6           |       |
| 20    | 3600 | 208-230/460 | 256JP | UJ20P1DP       | \$2,730 | DS-3PT          | 1.25 | 30.0              | 230           | 91.7           | 51-46/23       | 03,14 |
|       | 1800 | 208-230/460 | 256JP | UJ20P2DP       | \$2,463 | DS-3PT          | 1.25 | 30.0              | 230           | 93.0           | 53-47/23.5     | 03    |
|       | 1800 | 575         | 256JP | UJ20P2GP       | \$2,463 | DS-3PT          | 1.25 | 30.0              | 230           | 93.0           | 19             |       |
| 25    | 3600 | 208-230/460 | 256JP | UJ25P1DFP      | \$3,235 | DS-3PT          | 1.15 | 30.0              | 230           | 91.7           | 64-57/28.3     | 03,14 |
|       | 3600 | 208-230/460 | 284JP | UJ25P1DP       | \$3,595 | DS-3PT          | 1.25 | 32.0              | 280           | 91.7           | 65-57/28.4     | 03    |
|       | 1800 | 208-230/460 | 284JP | UJ25P2DP       | \$3,237 | DS-3PT          | 1.25 | 32.0              | 280           | 93.6           | 65-59/29.3     | 03    |
|       | 1800 | 575         | 284JP | HJ25P2GP       | \$3,237 | DS-3PT          | 1.15 | 30.8              | 380           | 93.6           | 23             |       |
| 30    | 1800 | 208-230/460 | 286JP | UJ30P2DP       | \$3,666 | DS-3PT          | 1.25 | 32.0              | 300           | 93.6           | 78-70/35       | 03    |
|       | 1800 | 575         | 286JP | HJ30P2GP       | \$3,666 | DS-3PT          | 1.15 | 30.8              | 410           | 93.6           | 27.6           |       |

Note 03 660/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz; 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 14 NEMA® Design A

† All marks shown within this document are properties of their respective owners.

# Special Application Close Coupled Pump Three Phase Totally Enclosed Fan Cooled (TEFC) Premium Efficient



UT4

## Westcoast Shaft - Footed

| HP    | RPM  | Voltage     | Frame  | Catalog Number | List    | Discount Symbol | SF   | "C" Dim. (inches) | Ship Wt (lbs) | Full Load Eff. | Full Load Amps | Notes |
|-------|------|-------------|--------|----------------|---------|-----------------|------|-------------------|---------------|----------------|----------------|-------|
| 7 1/2 | 3600 | 208-230/460 | 213TCZ | UJ7P1DJ        | \$1,345 | DS-3PT          | 1.25 | 22.8              | 105           | 91.0           | 19.9-17.8/8.9  | 03    |
|       | 1800 | 208-230/460 | 213TCZ | UJ7P2DJ        | \$1,228 | DS-3PT          | 1.25 | 22.8              | 105           | 91.7           | 20-18.2/9.1    | 03    |
| 10    | 3600 | 208-230/460 | 215TCZ | UJ10P1DJ       | \$1,556 | DS-3PT          | 1.25 | 24.3              | 120           | 91.0           | 26.4-23.5/11.7 | 03    |
|       | 1800 | 208-230/460 | 215TCZ | UJ10P2DJ       | \$1,458 | DS-3PT          | 1.25 | 24.3              | 120           | 91.0           | 26.4-23.5/11.7 | 03    |
| 15    | 3600 | 208-230/460 | 215TCZ | UJ15P1DFJ      | \$1,801 | DS-3PT          | 1.25 | 24.3              | 120           | 91.0           | 39-36/18       | 03,14 |

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 14 NEMA<sup>®</sup> Design A

# Special Application Close Coupled Pump Three Phase Open Drip Proof (ODP) NEMA<sup>®</sup> Premium Efficient



NEMA Premium

DE1, DE3, DE4, DEF4

## APPLICATIONS:

For the specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft. Used in damp, dusty or dirty environments.

## FEATURES:

- Class F Insulation, Class B Rise At Service Factor
- Rolled Steel Frame
- Aluminum End Shields 140-250, Cast Iron End Shields 280-320
- Oversized Ball Bearings w/Locked Shaft End Construction
- Premasked Mylar Nameplate (with "CE" Mark)
- F1 Assembly Position
- Regreasable Bearings 180 Frame & Up, Lifting Provisions 210 Frame & Up
- Double Shielded Bearings
- 40°C Ambient, NEMA<sup>®</sup> Design B Performance On 60 Hertz Sine Wave Power
- "JM" Shaft For Mechanical Seal
- "JM" Shaft on 210 Frame and Smaller; JP Shaft on 250 and 280 Frame

## JM Shaft - Footed

| HP    | RPM  | Voltage     | Frame | Catalog Number | List  | Discount Symbol | SF   | "C" Dim. (inches) | Ship Wt. (lbs) | Full Load Eff. | Full Load Amps | Notes        |
|-------|------|-------------|-------|----------------|-------|-----------------|------|-------------------|----------------|----------------|----------------|--------------|
| 3/4   | 1200 | 208-230/460 | 143JM | DJ34P3DM       | \$655 | DS-3POP         | 1.15 | 15.0              | 30             | 80.0           | 2.8-2.8/1.4    | 03           |
| 1     | 1800 | 200         | 143JM | DJ1P2HM        | \$487 | DS-3POP         | 1.15 | 15.0              | 30             | 85.5           | 3.6            |              |
|       | 1800 | 208-230/460 | 143JM | DJ1P2DM        | \$487 | DS-3POP         | 1.15 | 15.0              | 30             | 85.5           | 3.1-3.1/1.5    | 03           |
|       | 1200 | 208-230/460 | 145JM | DJ1P3DM        | \$655 | DS-3POP         | 1.15 | 15.0              | 35             | 82.5           | 4-4/2          | 03           |
| 1 1/2 | 3600 | 208-230/460 | 143JM | DJ32E1DM       | \$491 | DS-3FPO         | 1.15 | 15.0              | 30             | 82.5           | 4.3-4/2        | 03,16,NNP,LA |
|       | 3600 | 208-230/460 | 143JM | DJ32P1DM       | \$519 | DS-3POP         | 1.15 | 15.0              | 30             | 85.5           | 4.2-3.8/1.9    | 03           |
|       | 1800 | 200         | 145JM | DJ32P2HM       | \$513 | DS-3POP         | 1.15 | 15.0              | 35             | 86.5           | 4.8            |              |
|       | 1800 | 208-230/460 | 145JM | DJ32P2DM       | \$513 | DS-3POP         | 1.15 | 15.0              | 35             | 86.5           | 4.4-4.1/2.1    | 03           |
|       | 1200 | 208-230/460 | 182JM | DJ32P3DM       | \$660 | DS-3POP         | 1.15 | 16.0              | 50             | 86.5           | 5.2-5.3/2.6    | 03           |
| 2     | 3600 | 208-230/460 | 145JM | DJ2E1DM        | \$524 | DS-3FPO         | 1.15 | 15.0              | 35             | 84.0           | 5.6-5.1/2.5    | 03,16,NNP,LA |
|       | 3600 | 208-230/460 | 145JM | DJ2P1DM        | \$567 | DS-3POP         | 1.15 | 15.0              | 35             | 85.5           | 5.5-5/2.5      | 03           |
|       | 1800 | 200         | 145JM | DJ2P2HM        | \$563 | DS-3POP         | 1.15 | 15.0              | 35             | 86.5           | 6.3            |              |
|       | 1800 | 208-230/460 | 145JM | DJ2P2DM        | \$563 | DS-3POP         | 1.15 | 15.0              | 35             | 86.5           | 5.9-5.6/2.8    | 03           |
|       | 1800 | 575         | 145JM | DJ2E2GM        | \$482 | DS-3FPO         | 1.15 | 15.0              | 37             | 84.0           | 2.4            | NNP,LA       |
|       | 1800 | 575         | 145JM | DJ2P2GM        | \$563 | DS-3POP         | 1.15 | 15.0              | 35             | 85.5           | 2.2            |              |
|       | 1200 | 208-230/460 | 184JM | DJ2P3DM        | \$739 | DS-3POP         | 1.15 | 16.0              | 60             | 87.5           | 6.4-6.3/3.1    | 03           |
| 3     | 3600 | 208-230/460 | 145JM | DJ3P1DM        | \$582 | DS-3POP         | 1.15 | 15.0              | 35             | 85.5           | 8.3-7.4/3.7    | 03           |
|       | 1800 | 200         | 182JM | DJ3P2HM        | \$598 | DS-3POP         | 1.15 | 16.0              | 50             | 89.5           | 8.8            |              |
|       | 1800 | 208-230/460 | 182JM | DJ3P2DM        | \$598 | DS-3POP         | 1.15 | 16.0              | 50             | 89.5           | 8.3-7.7/3.8    | 03           |
|       | 1200 | 208-230/460 | 213JM | DJ3P3DM        | \$941 | DS-3POP         | 1.15 | 18.0              | 90             | 88.5           | 9.4-8.9/4.4    | 03           |

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 14 NEMA<sup>®</sup> Design A

Note 16 Motors marked 208-230/460 volts may not meet all NEMA (MG-1) performance standards when operated at 208 volts

Note LA Limited Availability

Note NNP Non-NEMA<sup>®</sup> Premium

† All marks shown within this document are properties of their respective owners.

BRAKEMOTORS  
GENERAL PURPOSE SINGLE PHASE  
HVAC  
WASHDOWN  
AGRICULTURE  
COMMERCIAL PUMP MOTORS  
CLOSE COUPLED PUMP MOTORS  
FIRE PUMP MOTORS  
POOL & SPA MOTORS  
RESIDENTIAL WATER PUMP  
ELEVATOR GATE & DOOR