

# Elevator and Gate & Door Motors

## SUBMERSIBLE AND DRY HYDRAULIC ELEVATOR MOTORS

**Horsepower:** 3 through 125 HP

**Frame Sizes:** 90 through 404T

**Phase:** Three Phase

**RPM:** 3600 or 1800 RPM

**Voltage:** 200, 208-230/460, 230/460, 460, 575

**Enclosure:**  
Open Drip Proof (ODP) on Dry Hydro

**Service Factor:**  
1.00 SF or greater

**Insulation:** Class B or F Insulation

**Efficiency:** Standard Efficient

**Agency:** UL<sup>®</sup> Recognized and  
CSA<sup>®</sup> Certified

## COMMERCIAL GATE AND DOOR MOTORS

**Horsepower:** 1/3 through 1 HP

**Phase:** Single and Three Phase

**RPM:** Single Speed 1725 RPM, Two Speed 1625/1325 RPM

### Voltage:

- Three Phase, 208/230-460
- Single Phase, 115/208-230
- Gate: Single Phase, Two Speed, 115 only

### Enclosure:

- Totally Enclosed Fan Cooled (TEFC) Three Phase
- Open Drip Proof (ODP) Single Phase

**Construction:** Rolled steel frame

### Mounting:

- Rigid Mount
- Resilient Mount
- C-Face Mount

**Bearings:** Permanently lubricated ball bearings

