



STANDARD LOCKED ROTOR & BREAKDOWN TORQUE

For pricing purposes, refer to the "Torque High" Option

HP	Standard Locked Rotor Torque (% of Full Load Torque)						
	3600	1800	1200	900	720	600	514
1	-	275	170	135	135	115	110
1.5	175	250	165	130	130	115	110
2	170	235	165	130	125	115	110
3	160	215	155	130	125	115	110
5	150	185	150	130	125	115	110
7.5	140	175	150	125	120	115	110
10	135	165	150	125	120	115	110
15	130	160	140	125	120	115	110
20	130	150	135	125	120	115	110
25	130	150	135	125	120	115	110
30	130	150	135	125	120	115	110
40	125	140	135	125	120	115	110
50	120	140	135	125	120	115	110
60	120	140	135	125	120	115	110
75	105	140	135	125	120	115	110
100	105	125	125	125	120	115	110
125	100	110	125	120	115	115	110
150	100	110	120	120	115	115	60
200	100	100	120	120	115	60	60
250	70	80	100	100	60	60	60
300	70	80	100	60	60	60	60
350	70	80	100	60	60	60	60
400	70	80	60	60	60	60	60

HP	Standard Breakdown Torque (% of Full Load Torque)						
	3600	1800	1200	900	720	600	514
1	-	300	265	215	200	200	200
1.5	250	280	250	210	200	200	200
2	240	270	240	210	200	200	200
3	230	250	230	205	200	200	200
5	215	225	215	205	200	200	200
7.5	200	215	200	200	200	200	200
10	200	200	200	200	200	200	200
15	200	200	200	200	200	200	200
20	200	200	200	200	200	200	200
25	200	200	200	200	200	200	200
30	200	200	200	200	200	200	200
40	200	200	200	200	200	200	200
50	200	200	200	200	200	200	200
60	200	200	200	200	200	200	200
75	200	200	200	200	200	200	200
100	200	200	200	200	200	200	200
125	200	200	200	200	200	200	200
150	200	200	200	200	200	200	175
200	200	200	200	200	200	175	175
250	175	175	175	175	175	175	175
300	175	175	175	175	175	175	175
350	175	175	175	175	175	175	175
400	175	175	175	175	175	175	175

† All marks shown within this document are properties of their respective owners.

