

FAST TRACK®

Engineered To Order Program

Engineer, build, and ship in three weeks for delivery in less than four weeks.

Now you can expect delivery of your 3-phase horizontal, 140 to 447 frame direct connect ETO motors in four weeks rather than eight weeks.

- 3 Phase Horizontal, 140 to 447 frame direct connect products are eligible
- 2, 4, 6, and 8 Pole
- Broad offering of options

ODP	STEEL EDGE™	UNIMOUNT®	Hostile Duty®
CORRO-DUTY®	841 PLUS®	661 PLUS®	Auto Duty
Haz. Loc.	Cooling Tower	Inverter Duty	CCP



FAST TRACK Options

Fast Track Options	Notes
Arctic Duty 140-400 frame	
Altitude	
Aluminum Fan	
Ambient	
Assembly Position (F1, F2, or F3)	Vertical and Wall Mount
Balance	Special and Precision
Bearing Life (Hours)	
Bearings, Roller	
Insulated bearings	Insulated shaft, Add one day (320 Frame and above)
Spare Set Of Bearings	
Brg Caps/Locked Brg	
Breather/Drains	
Main Conduit Box Size/Const	
Coupling Plate	
Accessory Conduit Box/Condulet	
Cast Iron Fan Cover	
Connection To Load	Direct, Belted, Chain
COS orders	
Direction Of Rotation	
Division 2 Non-Listed	
Dowel Pin Holes	
Drain Holes, Multiple	
Drip Cover	
Efficiency Class	
Endshields, C-Face	
Endshields, D-Flange	
Enclosure	ODP, TEFC, TENV, TEAO
Corro Duty / Severe Duty	
Marine Duty	
Tropical Protection	
Fire Pump Motor	
Fans	Aluminum
Frame Footless/Special Feet	
Foot Flatness, Special	
Frequency	
Grease	
Special	Contact CSR for availability.
Fittings	
High Temp	
Low Temp	
Grounding In Conduit Box	
Grounding On Frame	
Shaft Grounding Rings	Aegis SGR or Inpro CDR
Hardware, Stainless Steel	
High Inertia Load	
Insulation Class	

Fast Track Options	Notes
Insulation System	
Leads	
Lugs	
Extended (length)	
Sealed (Potted) Leads	Add one day
Positioning Gasket	
Lifting Lugs	
Multi-Speed	
Additional Nameplate	
Special I.D. Nameplate	
Add. Stamping On Std N/P(ASNP)	
Special Main N/P Data Format	
Paint, Special	Contact CSR for availability. Add 3 days.
Prints and Data	
Purge Ports	
Screens	
Sealant - RTV or Loctite	
Seals	Only Includes Shaft Slinger, Inpro Standard Material, Lip Seals and MGS
Service Factor	
Shafts	
Special Material	Stainless 303 only
Extended (length)	
Double extension	
Special Shaft Dimensions	Add one day
Space Heater and Accessories	Includes silicone rubber strip heaters and Thermostatically controlled. 115 and 230v only
Spare Parts	
Special Applications	Cooling Tower, Close-Coupled Pump
Starting Current, Lower than Std	
Starting Method	
Temperature Rise	
Thermal Prot. - Bearings	Platinum RTD Only
Thermal Protection - Windings	Platinum RTD Only, Thermostats 150C
Torque, High	
Testing (add up to 2 weeks)	Short Commercial Test (SCT) - Unwit SCT, Convert Data to 50Hz SCT, 50Hz up to 125HP IEEE841+ Enhanced No Load Test Vibration Test - Unwitnessed (IPS) Vibration Test - Unwitnessed (Mils) Polarization Index - Unwit Surge Tests Per 632179
Vertical Jacking Provisions	
Voltage	up to 690v
U-Frame (Automotive Duty)	
Vibration Detectors	Arrange to accommodate only



FAST TRACK Exclusions

Fast Track Options	Notes
Arctic Duty 440 Frame	
Blower Cooled Motors	
Brakes	
Bronze Fan	
Encoders & Detectors	Encoders, Vibration Detectors, Zero Speed Switch
Motor Tests	Testing not listed in included features are not available
Mount Customer Half Coupling	
Purge Ports	
Screens	Stainless Steel Screens
Special Applications	Crusher Duty, Belted loads
Special Bearings	Angular contact, ceramic insulated bearings, special lubrication, special bearing enclosures, CARB
Main Conduit Box Accessories	Space Heater in Conduit Box, Remote or Floor Mounting, Current Transformers, Special Connectors
Special Mounting	Slide Base, Slide Rails, Sole Plate
Special Shaft Seals	Any special materials, Garlock or taconite are excluded
Special Space Heater Requirements	Special temperature limits
ARRA Orders	
Lubrication, Oil Mist	
Special Lead Terminals	

Max quantities per order

Frame Size	Max Quantity
140 through 400 Frame (Motores)	10
440 Frame (Mena)	3

*please contact your CSR for capacity review if larger quantities are required.

**If material is not available to meet an order, your CSR will advise the earliest lead time possible within 3 days of placing an order.

Cancellation Policy

No cancellation will apply for orders cancelled within the first 3 days of order entry

If there is a lead-time change the customer will have option to cancel within 3 days of notification of revision without penalty. If a FasTrack order is entered, scheduled and cancelled by the customer on days 4 or 5 a penalty of 70% will be applied. A penalty of 100% will be applied for orders cancelled later than day five.

Nidec

NIDEC MOTOR CORPORATION

8050 W. Florissant Avenue | St. Louis, MO 63136
Phone: 888-637-7333 | Fax: 866-422-7758