

EZ-FIT[®] Motors

Condenser Fan and Direct Drive Blower Multi-Horsepower Motors



EZ-FIT condenser fan and direct drive blower motors deliver all the premium features of a multi-horsepower motor.

The versatility of the motor line eliminates the need for contractors to carry multiple motors – saving time, space and money.



Product Overview and Features

Multi-Horsepower Motors

EZ-FIT Condenser Fan

Horsepower: 1/2-1/8 HP

Speed: 1075 and 825 RPM

Rated Voltages: 208-230

Ambient Rating: 60°C/70°C (140°/158°F)

Enclosure: Totally Enclosed Air Over (TEAO)

Mounting: All position mounting, Rheem[®] Side Shell Holes; Select models include Rheem[®] and Trane[®] endshields

Warranty: One-year limited warranty from date of installation

Frame: 48



EZ-FIT Furnace and Air Handler Direct Drive Blower

Horsepower: 3/4-1/6 HP

Speed Range: 1075 RPM / 4 SPD

Ambient Rating: 40°C (104°F)

Enclosure: Open Air Over (OAO)

Rated Voltages: 115 and 208-230

Capacitor: Compatible with 370V (not included)

Mounting: Thru-Bolts, Rheem[®] Shell Holes or Belly Band; Extended Mounting Studs; 2.5" Dia. Hub Rings Included

Warranty: One-year limited warranty from date of installation



EZ-FIT Direct Drive Fan and Blower											
Catalog Number	HP	RPM	Voltage	Bearings	CAP MFD	Amps	Competitor Cross Reference		Mount	Ship Wt	Notes
							Packard	Mars			
3312	3/4-1/5	1075 / 4 SPD	115	Ball	20 MFD @ 370V	8.1-3.1	45470	10466	Stud	16.6	H40
3313	3/4-1/5	1075 / 4 SPD	208-230	Ball	20 MFD @ 370V	3.8	45471	10467	Stud	16.6	H40
3314	1/2-1/6	1075 / 4 SPD	115	SAB	10 MFD @ 370V	7.3-2.8	45460	10463	Stud	13.5	H40
3315	1/2-1/6	1075 / 4 SPD	208-230	SAB	10 MFD @ 370V	3.6	45461	10464	Stud	13.5	H40
EZ-FIT High Ambient Condenser 70°C											
1874H	1/4-1/8	825	208-230	Ball	5 MFD @ 370V	2.1		20459	Stud	13.27	H25
1875H	1/3-1/5	825	208-230	Ball	7.5 MFD @ 440V	2.4-1.4	45488BF	20469	Stud	18.4	H25
3323H	1/3-1/6	1075	208-230	Ball	7.5 MFD @ 370V	2	45458BF	20465	Stud	13.65	H25
3325H*	1/2-1/5	1075	208-230	Ball	15 MFD @ 370V	2.6-1.7		20468	Stud	16.6	H25
EZ-FIT Condenser 60°C											
1874	1/4-1/8	825	208-230	SAB	5 MFD @ 370V	2		10459	Stud	11	H25
1875	1/3-1/5	825	208-230	SAB	7.5 MFD @ 440V	2.4-1.4	45488B	10469	Stud	17	H25
3323	1/3-1/6	1075	208-230	Ball	7.5 MFD @ 370V	2	45458B	10465	Stud	13.65	H25
3325*	1/2-1/5	1075	208-230	Ball	15 MFD @ 370V	2.6-1.7		10468	Stud	16.6	H25

Note H40 Screws for Shell Mounting Included in Carton
 Note H25 Includes 4 Holes With Screws In Shell For RHEEM[®] Mount
 * Includes Rheem[®] and Trane[®] Endshield Mounting Holes



8050 W. Florissant Avenue | St. Louis, MO 63136

† All marks shown within this document are properties of their respective owners.

Nidec Motor Corporation, © 2017; All Rights Reserved. U.S. MOTORS[®] is a registered trademark of Nidec Motor Corporation. Nidec Motor Corporation trademarks followed by the ® symbol are registered with the U.S. Patent and Trademark Office.

HVACR Aftermarket Customer Service
 Phone: 855-487-6686 | Fax: 800-899-2887