RESCUE® EZ-Wire™ Motor



EZ-Wire[™] Condenser

Horsepower: 1/3-1/8 HP Speed: 1075 and 825 RPM Rated Voltage: 208-230V Ambient Rating: 80°C (176°F)

Frame: 48

Enclosure: Totally Enclosed Air Over (TEAO)

Mounting: All position mount, extended mounting studs

and Rheem Side Shell Holes





EZ-Wire Condenser									
Catalog Number	HP	RPM	Voltage	Amps	Leads	Capacitor			
5430	1/3-1/6	1075	208-230	2.2	48"	7.5 MFD @ 440V			
5431	1/4-1/8	825	208-230	2.1	48"	7.5 MFD @ 440V			

EZ-Wire™ Direct Drive and Blower

Horsepower: 1/2 HP Speed: 1075/4 SPD

Rated Voltage: 115 or 208-230V Ambient Rating: 40°C (104°F)

Frame: 48

Enclosure: Open Air Over (OAO)

Mounting: All position mount and

Rheem Side Shell Holes





EZ-Wire Condenser									
Catalog Number	HP	RPM	Voltage	Amps	Leads	Capacitor			
5432	1/2	1075/4 SPD	115	7.3	36"	10/7.5 MFD @ 370V			
5433	1/2	1075/4 SPD	208-230	3.6	36"	10/5 MFD @ 370V			

Product Overview and Options


Our motors bring all the value that you expect from the U.S. MOTORS® brand:

- Ball Bearings Durability for high temperature applications for longer life than traditional sleeve bearings
- Special Rotor Corrosion Protection Designed for longer life and sure start-ups season after season
- Reversible Easy to change quick connect terminals for application flexibility
- Capacitors USA made capacitors included

Order One of Three Ways (5430 example below)



Catalog Number: 5430-SKD, 5431-SKD, 5432-SKD, 5433-SKD Market motors on your floor for maximum visibility 90 per skid



Catalog Number: 5430, 5431, 5432, 5433 Convenient 3-pack for additional smaller displays

Full Skid of 90 motors in 3-pack form (Skid = 30 3-packs)

