


Three Phase Fan Duty Totally Enclose Air Over (TEAO)

FSN,
SN

APPLICATIONS:

Desinged for use in commercial evaporative coolers - 100% humidity and occasional below freezing temperatures.

FEATURES:

- Class F Insultation, 40C Ambient
- Double Sealed Ball Bearings
- Low Temp Grease; -50C For 182T - 213T Frames
- Rolled Steel Frame 56- 213T ; Cast Aluminum End Shields
- 1.15 Service Factor
- NEMA® Design B Performance on 60 Hz Sine Wave Power,
- All 230/460 Volt Also Rated for 190/380 Volts (56 & 56H Frames Only),
- Conduit Box Assembly Position
- * F3 Standard For 145T - 213T Frames
- * Conduit In End Shield for 56 & 56H Frames
- Cast Aluminum End Shields

HP	RPM	Volts	Frame	Catalog Number	List	Multiplier Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Amps	Notes
1/4	1200	208-230/460	56	SV14SA3DR	\$372	DS-3RM	1.15	10.3	17	1.9/1.0	24
1/3	1200	208-230/460	56	SV13SA3DR	\$382	DS-3RM	1.15	10.3	23	1.9/0.9	24
1/2	1200	208-230/460	56	SV12SA3DR	\$402	DS-3RM	1.15	10.3	26	2.4/1.2	24
	900	208-230/460	56H	SV12SA4D	\$498	DS-3RM	1.15	13.3	28	4.3/2.1	24
3/4	1200	208-230/460	56H	SV34SA3D	\$446	DS-3RM	1.15	11.3	27	3.6/1.9	24
	900	208-230/460	56H	SV34SA4D	\$507	DS-3RM	1.15	13.3	29	4.5/2.3	24
1	1200	208-230/460	56H	SV1EA3D	\$476	DS-3RM	1.15	12.1	31	3.7/1.9	24
	900	208-230/460	56H	SV1EA4D	\$514	DS-3RM	1.15	13.3	33	5.0/2.5	24
1-1/2	1200	230/460	182T	SV32E3E3	\$1,209	DS-3RM	1.15	12.9	64	5.4/2.7	
2	1800	208-230-460	56H	SV2E2D	\$480	DS-3RM	1.15	13.1	35	6.2/3.1	24
	1200	230/460	184T	SV2E3E3	\$1,230	DS-3RM	1.15	13.9	74	6.8/3.4	
3	1200	230/460	213T	SV3E3E3	\$1,531	DS-3RM	1.15	15.8	80	9.1/4.5	
5	1800	230/460	184T	SV5E2E3	\$1,038	DS-3RM	1.15	13.9	65	12.7/6.3	
7-1/2	1800	230/460	213T	SV7E2E3	\$1,492	DS-3RM	1.15	15.8	90	18.7/9.3	

Note 24 Automatic Reset Thermal Overload Protector

