

## Thru-Bolt Pool & Spa 6.5" Frame Diameter



### FEATURES:

- Open Drip Proof
- Thru-Bolt Mount
- Class F Insulated
- 1081 & 1563 Design
- Sealed Ball Bearing
- Rigid Base
- Thermally Protected
- 60°C Ambient
- 3 o'clock Conduit
- Premium Energy Efficient Design
- Shaft Thread - 3/8-16 UNC-2A
- **Discount Symbol: DS-FPS**

### extreme-E Premium Energy Efficient, Single Speed, Switchless Design

HP	SF	THP	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.	Notes	List
1.5	1.00	1.50	3450	230/115	60	8.8/17.5	ASB602	56Y	9.58	28	1	\$171
2.0	1.00	2.00	3450	230	60	10.0	ASB603	56Y	9.58	28		\$188
2.5	1.00	2.50	3450	230	60	10.5	ASB604	56Y	9.58	30		\$199
3.0	1.00	3.00	3450	230	60	12.0	ASB605	56Y	10.08	33		\$208
4.0	1.00	4.00	3450	230	60	16.4	ASB606	56Y	10.58	37		\$237

### extreme-E Premium Energy Efficient, Two Speed, Soft Start

HP	SF	THP	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.	Notes	List
1.5/1.8	1.00	1.5/1.8	3450/1725	230	60	8.0/3.0	ASB502	56Y	9.58	31		\$189
2.0/2.5	1.00	2.0/2.5	3450/1725	230	60	10.0/3.5	ASB503	56Y	10.08	35		\$196
2.5/3.3	1.00	2.5/3.3	3450/1725	230	60	10.5/3.8	ASB504	56Y	10.33	38		\$207
3.0/3.8	1.00	3.0/3.8	3450/1725	230	60	12.0/4.4	ASB505	56Y	10.83	36		\$218
4.0/5.0	1.00	4.0/5.0	3450/1725	230	60	16.4/4.8	ASB506	56Y	11.58	45		\$245
5.0/6.3	1.00	5.0/6.3	3450/1725	230	60	19.5/5.0	TT507	56Y	12.08	48		\$512

#### NOTE:

1) Capacitor start design

Note: Contact dealer for full conditions of operation  
Catalog numbers are for competitive comparison purposes only.



Extreme-E<sup>®</sup> represents one of our most efficient running, highest performing lines of motors.

