

Special Application Single Phase, Open Drip Proof (ODP) Jet Pump, Square Flange & C-Face Capacitor Start



APPLICATIONS:

For jet pumps, booster pumps, centrifugal pumps, lawn sprinkler pumps.

FEATURES:

- 303 Stainless Steel Shaft
- C-Face: 7/16-20 UNF2A Thread
- Square Flange: 1/2-20 UNC-2A Thread
- Ball Bearings (Locked Drive End Bearing)
- Continuous Duty
- 60 Hertz
- EZ-Access™ Motor Cover
- 40°C Ambient
- Automatic Reset Thermal Overload Protector
- Round Frame (Without Base), NEMA® 56C C-Face or Square Flange Mounting
- Power Leads Supplied For Proper Connection To Pressure Switch
- Voltage Selector Switch (Catalog Numbers Ending With "-2V" and "UPR")

C-Face, Two Compartment Product, EZ-Access™ Motors

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Amps	Notes
1/2	3600	115/230	56J	JJ0502-2V	\$199	DS-3FJP	1.6	13.0	16.5	6.8/3.4	-
3/4	3600	115/230	56J	JJ0752-2V	\$212	DS-3FJP	1.5	13.0	19.65	10.6/5.4	-
1	3600	115/230	56J	JJ1002-2V	\$238	DS-3FJP	1.6	14.0	24.68	13.6/6.6	-
1 1/2	3600	115/230	56J	JJ1502-2V	\$301	DS-3FJP	1.6	14.3	27.07	12.5/6.5	18
2	3600	230	56J	JJ2002-2	\$360	DS-3FJP	1.4	15.5	31.3	8.6	18

Square Flange, Two Compartment Product, EZ-Access™ Motors

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Amps	Notes
1/2	3600	115/230	48Y	JS0502-2V	\$199	DS-3FJP	1.9	12.8	16.17	8.4/4.2	-
3/4	3600	115/230	48Y	JS0752-2V	\$212	DS-3FJP	1.65	13.3	22.16	11.6/5.8	-
1	3600	115/230	48Y	JS1002-2V	\$238	DS-3FJP	1.65	13.3	23.89	13.5/7.0	-
1 1/2	3600	115/230	48Y	JS1502-2V	\$301	DS-3FJP	1.5	13.5	28	13.5/7.0	18
2	3600	230	48Y	JS2002-2	\$360	DS-3FJP	1.3	13.5	27.42	11.0	18

Note 18 Incorporates Run Capacitor

